





DOF-0-212D(98.02)




△
特別管理品目
SPECIAL CONTROL ITEM
M X 2 5

DETAIL A
(SCALE 10:1)



版数 REV.	年月日 DATE	図面 NO.	変更内容 DESCRIPTION	製図 DR.	担当 CHK.	査閲 APPD.	承認 APPD.
2	25.Jan.2002	49406	CHANGED SPECIAL CONTROL ITEM AND NOTE.	H.ITAKURA	N.OGAWA	—	T.Totani



NOTE1.THIS PART IS M25P10K4F1 MADE BY JAE.

△ 2.APPLICABLE WIRE:1.5DS-0XC-SP(MAKER:Sumitomo Electric Industries,Ltd.)
AND RG-174(MAKER:Fujikura,Ltd.)

3.THE SHEARED EDGES OF CONTACT SHALL NOT BE PLATED.

4.PART NUMBER & QUANTITY SHALL BE DESCRIBED AS INDICATED.

注1.本製品は日本航空電子工業(株)のM25P10K4F1である。

△ 2.適用電線サイズは1.5DS-0XC-SP(住友電気工業(株)製)及びRG-174((株)フジクラ製)である。

3.破断面にはめっきはつかない。

4.図示の位置に品名・数量を記載する。

3	PIN INNER CONTACT	10,000	HIGH CONDUCTIVITY COPPER ALLOY	TIN PLATING	
2	TAPE	1	PAPER		
1	REEL	1	PAPER		
符号 NO.	名称 DESCRIPTION	個数 QTY.	材料 MATERIAL	仕上 FINISH	備考 REMARKS
仕様書(SPECIFICATION)	JACS-1657	第1版(ORIGINAL DATE) 22.Aug.2001	製図 DR. M.TANAKA	1:5	日本航空電子工業株式会社
公差(GENERAL TOLERANCE)			担当 CHK. N.OGAWA	名称(TITLE) M25P10K4F1	JAE ELECTRONICS INDUSTRY, LTD.
寸法(DIMENSION)			査閲 APPD. 	(PIN INNER CONTACT)	図面番号(DRAWING NO.)
	±0.3	° ±	承認 APPD. T.TOTANI	重量(WEIGHT)	SJ035767
	× ±0.3	°× ±			
	×× ±0.3				
	××× ±				

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[JAE Electronics:](#)

[M25P10K4F1](#)