

**Main**

Range	Linergy
Product name	FT
Device short name	GV2G
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	3P
Range compatibility	TeSys - GV2 TeSys - U TeSys - D TeSys - K
Number of tap-offs	4
[Ith] conventional free air thermal current	63 A
Connection pitch	2.13 in (54 mm)

**Complementary**

Mounting location	On terminal
[Ui] rated insulation voltage	690 V
Length	8.5 in (216 mm)
Product weight	0.19 lb(US) (0.085 kg)

**Environment**


**Offer Sustainability**

Green Premium product	Green Premium product
Compliant - since 0640 - Schneider Electric declaration of conformity	Compliant - since 0640 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

**Contractual warranty**

Warranty period	18 months
-----------------	-----------

**Sets of Busbars GV2G445, GV2G454, GV2G472, with Terminal Block GV2G05**



	l	p
GV2G445 (4 x 45 mm)	179	45

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

GV2G454 (4 x 54 mm)	206	54
GV2G472 (4 x 72 mm)	260	72

Number of tap-offs	a			
	5	6	7	8
GV2G445	224	269	314	359
GV2G454	260	314	368	422
GV2G472	332	404	476	548