

ROHS COMPLIANT

PRODUCT DATA DRAWING

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
-	DCN 42145	03/16	DAL

RP

RP

OAL ± TOL.

OAL		TOL.
FROM:	TO:	
MIN	11.900"	± .100"
12.000"	99.900"	± .500"

MATERIAL:

CONNECTORS :

CABLE:

SHRINK TUBING:

PERFORMANCE:

IMPEDANCE:

FREQ. RANGE:

SEE NOTES

SEE NOTES

N/A

PROPRIETARY

50 OHMS

DC TO 26.5 GHz

NOTES:

1. PART NUMBERS TO BE 7032-6728-XXX. (XXX TO BE LENGTH).

2. EXAMPLE, 7032-6728-121 WILL BE A 12.100" CABLE ASSEMBLY.

MATERIAL: SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/64 ANGULAR: X° ±1°0' X°X' ±15' DECIMAL: .X ±.030 .XX ±.010 .XXX ±.005 INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994	UNLESS OTHERWISE SPECIFIED 1) ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES .005 R. MAX. 4) CHAM. 1ST & LAST THREADS. 5) SURFACE ROUGHNESS 63+MIL-STD-10. 6) DIA.'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R. 7) REMOVE ALL BURRS	TITLE: SMPM FEMALE VITA SNAP-IN TO SMA MALE Ø.047 CABLE ASSEMBLY	
			SIZE B	CAGE CODE 95077
			DWG. NO. 7032-6728-XXX	
			SCALE: 3:1	
THIRD ANGLE PROJECTION		DRAWN: ELA 03/07/16	SHEET 1 OF 1	
		CHECKED: DAL 03/07/16		
		APPROVED: DAL 03/07/16		