

1

2

3

4

5

6

7

8

REV.

EGN NO.

DATE

SIGN

DESCRIPTION

Conn.2

45°

M12\*1.0

12 Connector

13 Screw Nut

55.9

11 Cable

SS-050500-MF0-TSAXX

XX:01~99Meter

01:01Meter

02:02Meters

:

:

99:99Meters

99:99Meters

Cable Length(L):01~99Meters

LTW

9 Inner Mold

10 Outer Mold

Color: Black

4~8 Wire Harness

1 Connector

2 Screw Nut

3 Ring

Conn.1

45°

Conn.1

Conn.1

1

2

3

4

5

Conn.2

1

2

3

4

5

Pin Assignments

Front View

Pin Assignments

Front View

UNIT:mm

1

2

3

4

5

1

2

3

4

5

TOLERANCE

±0.5 mm

TITLE

M12 Conn T Cable Screw

SCALE

Free

MF Conn MF Pin

REV.

A

SIZE

A4

QC

inspection item

ITEM NO

DWG NO

CUSTOMER

DRAWN BY

CHECKED BY

APPROVED BY

DATE

DATE

DATE

Amphenol LTW

安費諾亮泰企業股份有限公司

Conn.1

5

Green

5

Conn.1

4

Black

4

Conn.1

3

Blue

3

Conn.1

2

White

2

Conn.1

1

Brown

1

Conn.1

Wire Color

Conn.2

Pin Out

Note:

\* QC Important Dimension.

\* Waterproof Rate: IP68

\* Housing: Black, PU

\* Male & Female Pin: Copper Alloy, Gold Plated

\* Wire Harness: UL1007 24AWG, 5Pcs.

\* Cable: UL2464 22AWG\*5C+Talc

\* Cable, PVC Jacket UV Resistant OD=5.5mm

\* Cable Length Tolerance: 1M~10M±5%mm, 11M~99±500mm.

ALTW

DCC. DEPT.

CONFIDENTIAL

2008.01.31

ISSUED

ALTW

R&D DEPT.

CONFIDENTIAL

2007.11.29

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

8 FMM0702-01-01A2