

			<table><tr><th colspan="4">REVISIONS</th></tr><tr><th>REV</th><th>DESCRIPTION</th><th>DATE</th><th>APPROVED</th></tr><tr><td>010</td><td>RELEASED</td><td>PATLAN 2/13/2008</td><td>[Signature]</td></tr></table>				REVISIONS				REV	DESCRIPTION	DATE	APPROVED	010	RELEASED	PATLAN 2/13/2008	[Signature]																																																																										
			REVISIONS																																																																																									
			REV	DESCRIPTION	DATE	APPROVED																																																																																						
010	RELEASED	PATLAN 2/13/2008	[Signature]																																																																																									
<table><tr><td colspan="2">DESIGNED FOR USE WITH</td></tr><tr><td colspan="2">RG 174, 316/U CABLE</td></tr><tr><td colspan="2">CABLE ENTRY DIAMETER</td></tr><tr><td colspan="2">MINIMUM</td></tr><tr><td>SLEEVE</td><td>.067</td></tr><tr><td>CONTACT</td><td>.021</td></tr></table>				DESIGNED FOR USE WITH		RG 174, 316/U CABLE		CABLE ENTRY DIAMETER		MINIMUM		SLEEVE	.067	CONTACT	.021																																																																													
DESIGNED FOR USE WITH																																																																																												
RG 174, 316/U CABLE																																																																																												
CABLE ENTRY DIAMETER																																																																																												
MINIMUM																																																																																												
SLEEVE	.067																																																																																											
CONTACT	.021																																																																																											
<table><tr><th>ELECTRICAL</th><th>MECHANICAL</th><th>ENVIRONMENTAL</th></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions MIL-STD-348A, Fig. 310.2</td><td>Temperature Rating -65°C To +165°C</td></tr><tr><td>Frequency Range (GHz) DC to 3.0</td><td>Recommended Mating Torque N/A</td><td>Vibration MIL-STD-202, Method 204, Condition D</td></tr><tr><td>Volt Rating (VRMS MAX) @ Sea Level 250</td><td>Mating Characteristics: Insertion (MAX Lbs) 3</td><td>Shock MIL-STD-202, Method 213, Condition I</td></tr><tr><td>VSWR -- 1.15 + .01 X (f GHz)</td><td>Withdrawal (MIN Oz) 1</td><td>Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C</td></tr><tr><td>Insertion Loss .06 V/F (GHz)</td><td>Force to Engage and Disengage (In-Lbs MAX) 2</td><td>Moisture Resistance MIL-STD-202, Method 106</td></tr><tr><td>RF Leakage (dB MIN) -60dB Min @ 2-3 GHz</td><td>Center Contact Captivation Axial (Lbs) 6.0 MIN</td><td>Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray</td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 190</td><td>Radial (In-Oz) N/A</td><td></td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750</td><td>Cable Retention Axial Force (Lbs) 20 MIN</td><td></td></tr><tr><td>Contact Resistance (Milliohms MAX) Center Contact 3.0</td><td>Torque (In-Oz) N/A</td><td></td></tr><tr><td>Outer Contact 2.0</td><td>Weight (Grams) TBD</td><td></td></tr><tr><td>Cable to Housing .05</td><td></td><td></td></tr><tr><td>RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500</td><td></td><td></td></tr><tr><td>I.R.(Megohms MIN) 10,000</td><td></td><td></td></tr></table>	ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.2	Temperature Rating -65°C To +165°C	Frequency Range (GHz) DC to 3.0	Recommended Mating Torque N/A	Vibration MIL-STD-202, Method 204, Condition D	Volt Rating (VRMS MAX) @ Sea Level 250	Mating Characteristics: Insertion (MAX Lbs) 3	Shock MIL-STD-202, Method 213, Condition I	VSWR -- 1.15 + .01 X (f GHz)	Withdrawal (MIN Oz) 1	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C	Insertion Loss .06 V/F (GHz)	Force to Engage and Disengage (In-Lbs MAX) 2	Moisture Resistance MIL-STD-202, Method 106	RF Leakage (dB MIN) -60dB Min @ 2-3 GHz	Center Contact Captivation Axial (Lbs) 6.0 MIN	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	Corona, 70,000 Ft (VRMS MIN) 190	Radial (In-Oz) N/A		Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750	Cable Retention Axial Force (Lbs) 20 MIN		Contact Resistance (Milliohms MAX) Center Contact 3.0	Torque (In-Oz) N/A		Outer Contact 2.0	Weight (Grams) TBD		Cable to Housing .05			RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500			I.R.(Megohms MIN) 10,000			<table><tr><td>HOUSING COUPLING NUT</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>PASSIVATE PER QQ-P-35</td></tr><tr><td>DIELECTRIC</td><td>PTFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>FERRULE</td><td>COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>REAR DIELECTRIC</td><td>NYLON</td><td>N/A</td></tr><tr><td>COMPONENT</td><td>MATERIAL</td><td>FINISH</td></tr></table>	HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35	DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204	REAR DIELECTRIC	NYLON	N/A	COMPONENT	MATERIAL	FINISH	<table><tr><td colspan="2">UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES</td><td colspan="2">DRAWN BY PATLAN DATE 2/12/98</td><td rowspan="3"></td><td rowspan="3">AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599</td></tr><tr><td colspan="2">CHECKED BY</td><td colspan="2">APPD BY [Signature] 4/3/98</td></tr><tr><td colspan="2">NO. AP. 20-530 408-04927</td><td colspan="2">USE ASS'Y PROCEDURE</td></tr><tr><td colspan="2">These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.</td><td colspan="2">TITLE OSM FLANGE MOUNT CABLE JACK-SOLDER ATTACHMENT M39012/58-3007 CATA</td><td>SIZE B</td><td>CODE IDENT NO. 26805</td><td>2036-8007-92</td><td>REV 010</td></tr><tr><td colspan="2"></td><td colspan="2">SCALE 4 : 1</td><td colspan="2"></td><td colspan="2">SHEET 1 OF 1</td></tr></table>	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		DRAWN BY PATLAN DATE 2/12/98			AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	CHECKED BY		APPD BY [Signature] 4/3/98		NO. AP. 20-530 408-04927		USE ASS'Y PROCEDURE		These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.		TITLE OSM FLANGE MOUNT CABLE JACK-SOLDER ATTACHMENT M39012/58-3007 CATA		SIZE B	CODE IDENT NO. 26805	2036-8007-92	REV 010			SCALE 4 : 1				SHEET 1 OF 1	
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																																																																										
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.2	Temperature Rating -65°C To +165°C																																																																																										
Frequency Range (GHz) DC to 3.0	Recommended Mating Torque N/A	Vibration MIL-STD-202, Method 204, Condition D																																																																																										
Volt Rating (VRMS MAX) @ Sea Level 250	Mating Characteristics: Insertion (MAX Lbs) 3	Shock MIL-STD-202, Method 213, Condition I																																																																																										
VSWR -- 1.15 + .01 X (f GHz)	Withdrawal (MIN Oz) 1	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C																																																																																										
Insertion Loss .06 V/F (GHz)	Force to Engage and Disengage (In-Lbs MAX) 2	Moisture Resistance MIL-STD-202, Method 106																																																																																										
RF Leakage (dB MIN) -60dB Min @ 2-3 GHz	Center Contact Captivation Axial (Lbs) 6.0 MIN	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray																																																																																										
Corona, 70,000 Ft (VRMS MIN) 190	Radial (In-Oz) N/A																																																																																											
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750	Cable Retention Axial Force (Lbs) 20 MIN																																																																																											
Contact Resistance (Milliohms MAX) Center Contact 3.0	Torque (In-Oz) N/A																																																																																											
Outer Contact 2.0	Weight (Grams) TBD																																																																																											
Cable to Housing .05																																																																																												
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500																																																																																												
I.R.(Megohms MIN) 10,000																																																																																												
HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35																																																																																										
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A																																																																																										
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																																																										
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204																																																																																										
REAR DIELECTRIC	NYLON	N/A																																																																																										
COMPONENT	MATERIAL	FINISH																																																																																										
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		DRAWN BY PATLAN DATE 2/12/98			AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599																																																																																							
CHECKED BY		APPD BY [Signature] 4/3/98																																																																																										
NO. AP. 20-530 408-04927		USE ASS'Y PROCEDURE																																																																																										
These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.		TITLE OSM FLANGE MOUNT CABLE JACK-SOLDER ATTACHMENT M39012/58-3007 CATA		SIZE B	CODE IDENT NO. 26805	2036-8007-92	REV 010																																																																																					
		SCALE 4 : 1				SHEET 1 OF 1																																																																																						