

## Test adapter - PAI-4-FIX-5/6 GY - 3035982

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

The figure shows the version in orange

### Product Features

- Make contact and latch securely to any point in the function shaft
- Test adapter for accommodating safety test plugs with a 4 mm diameter



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 10 pc    |
| Weight per Piece (excluding packing) | 1.43 g   |
| Custom tariff number                 | 85366990 |
| Country of origin                    | Poland   |

### Technical data

#### Dimensions

|              |          |
|--------------|----------|
| Height       | 45.30 mm |
| Length       | 5.8 mm   |
| Width        | 5.8 mm   |
| Diameter     | 5.80 mm  |
| Pin diameter | 2.40 mm  |

#### General

|       |                                                                                            |
|-------|--------------------------------------------------------------------------------------------|
| Note  | Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in |
|       | Do not plug in while the power is connected                                                |
| Color | gray                                                                                       |

# Test adapter - PAI-4-FIX-5/6 GY - 3035982

## Technical data

|                                 |        |
|---------------------------------|--------|
| Ambient temperature (operation) | 125 °C |
|---------------------------------|--------|

## Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V0 |
|----------------------------------------|----|

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141127 |
| eCl@ss 4.1 | 27141127 |
| eCl@ss 5.0 | 27141127 |
| eCl@ss 5.1 | 27141111 |
| eCl@ss 6.0 | 27141148 |
| eCl@ss 7.0 | 27141148 |
| eCl@ss 8.0 | 27440313 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC002255 |
| ETIM 5.0 | EC002255 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211812 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121411 |
| UNSPSC 12.01  | 39121411 |
| UNSPSC 13.2   | 39121411 |

## Approvals

### Approvals

Approvals

EAC / EAC

Ex Approvals

## Test adapter - PAI-4-FIX-5/6 GY - 3035982

### Approvals

Approvals submitted

---

#### Approval details

|     |
|-----|
| EAC |
|-----|

|     |
|-----|
| EAC |
|-----|