



NET IMPEDANCE (Z)						
Frequency	0.5 MHz	1 MHz	5 MHz	10 MHz	25 MHz	
Nominal (REF)	50 Ω	60 Ω	42 Ω	39 Ω	35 Ω	
Minimum	38 Ω	45 Ω	33 Ω	29 Ω	26 Ω	

**PRELIMINARY
PRINT**

FERRITE CORE DIMENSIONS (SPEC): mm [in]

A	32.00 [1.260]	+	0.60 [.024]
B	18.20 [.717]	+	0.40 [.016]
C	38.00 [1.496]	+	0.60 [.024]
D	8.00 [.315]	+	0.20 [.008]
E	4.00 [.157]	+	0.25 [.010]

WEIGHT/1000 33.30 kgs [73.40 Lbs]

NOTES: UNLESS OTHERWISE SPECIFIED

1. COSMETIC SPECIFICATION REFER TO WI-QA-038.
2. THE CONTACT SURFACE NEED TO BE POLISHED.



DIMENSIONS ARE IN mm[INCHES].				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.		Laird	
				PROJECT/PART NUMBER:	REV	PART TYPE:	DRAWN BY:
P3	ADD Z SPEC	03/06/18	Jcai	35U1260-320	P3	CNZ CORE	QIU
P2	CHANGE C	01/12/18	QIU	DATE:	SCALE:	MATERIAL:	
P1	PRELIMINARY DRAFT	12/21/17	QIU	12/21/17	1 : 1	Ferrite	
REV	DESCRIPTION	DATE	INT	CAD # 35U1260-320-P3	TOOL # U1260		