

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	05JUL2015	DL	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:
 BODY MATERIAL: DIE CAST ALUMINIUM ALLOY
 SURFACE TREATMENT: POWDER-COATED, GRAY
 OPERATION TEMPERATURE: -40-+125°C
 DEGREE OF PROTECTION: IP65 (MATED)

注释:

1. 技术参数:
 主体材料: 铝合金
 表面处理: 粉末喷涂, 灰色
 工作温度: -40-+125°C
 防护等级: IP65(配合)

TI450160121-000	H16B-SGR-BO-PG21	PG21	-
TI450160125-000	H16B-SGR-BO-M25	M25	-
TI450160221-000	H16B-SGR-BO-2PG21	PG21	PG21
TI450162125-000	H16B-SGR-BO-PG21/M25	PG21	M25
ASSEMBLY PART NUMBER	ASSEMBLY PART DESCRIPTION	IG1	IG2

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 05JUL2015

DAVID LI

CHK 05JUL2015

CHRIS WANG

APVD 05JUL2015

XU XIANG

PRODUCT SPEC

108-137013

APPLICATION SPEC

114-137013

WEIGHT -

CUSTOMER DRAWING

NAME
H16B-SGR-BO-PG/M

TE Connectivity

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-

MATERIAL
TBD

FINISH

-

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A3 - C-TI45016XXXX000 -

SCALE 3:5 SHEET 1 OF 1 REV A

1470-19 (3/13)