

## SmartOnline 120V 1kVA 900W Double-Conversion UPS, Tower, Extended Run, Network Card Options, LCD, USB, DB9 Serial

MODEL NUMBER: **SU1000XLCD**



### Highlights

- 1000VA / 1kVA / 900 watt on-line double-conversion tower UPS
- 100/110/120/127V 50/60Hz output, high efficiency economy mode option
- Interactive LCD with 10 selectable screens of UPS and site power data
- Expandable runtime, Hot-swappable batteries
- USB, RS232 & EPO ports, Network Management Card options
- 2 independently switched load banks
- NEMA 5-15P input; 6 5-15R outlets

### Package Includes

- SU1000XLCD SmartOnline® Tower UPS System
- USB, DB9 and EPO Cables
- Owner's Manual

### Description

Do you need to protect small- to medium-size servers, networking equipment and telecom systems against data loss, downtime and equipment damage due to power outages, voltage fluctuations and transient surges? Tripp Lite's SU1000XLCD SmartOnline® Tower UPS System is the solution! Featuring a 1000VA/900W capacity and true on-line operation with pure sine wave output and zero transfer time to battery, it provides the highest level of power protection for mission-critical equipment. The SU1000XLCD's large internal battery set supports connected equipment during blackouts, and runtime is expandable with optional external battery packs (Tripp Lite model [BP24V15RT2U](#), [BP24V28-2U](#) or [BP24V70-3U](#)), sold separately. The SU1000XLCD has 6 5-15R outlets, including 2 single-outlet load banks that are individually controllable to reboot select equipment on demand or maximize battery runtime for mission-critical equipment. USB and DB9 communication ports support messaging of detailed UPS operational parameters and line power status. PowerAlert UPS management software is available via free download. It comes backed by \$250,000 of Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

### Features

#### Ideal for Protection of Mission-Critical Equipment

The SU1000XLCD provides true on-line operation, reliable battery backup and comprehensive power management capability in a compact tower form factor. Featuring a 1000VA/900W capacity, 6 5-15R outlets, a 10-ft. cord with standard 5-15P plug, USB/DB9 ports and a slot for an optional network management accessory card, the SU1000XLCD offers a complete power protection solution for small- to medium-size servers, storage devices, telecom systems and other mission-critical equipment.

#### True On-Line Operation with Pure Sine Wave Output and Zero Transfer Time

The SU1000XLCD provides the highest level of protection available for mission-critical equipment. It actively converts raw incoming AC power to DC, then re-converts it back to regulated, filtered AC output with a pure sine wave, completely isolating connected components from all power problems. Zero transfer time between AC and battery operation maintains continuous output and further protects connected equipment from the disruptive effects of blackouts and severe low-voltage conditions. Sine wave output guarantees compatibility with all equipment types.

#### Individually Controllable Outlets



The SU1000XLCD includes 2 single-outlet load banks that are individually controllable via a software interface for remote reboot of locked-up equipment or load shedding to maximize battery backup time for mission-critical equipment.

#### **Reliable, Expandable Battery Backup**

UPS battery backup keeps connected equipment operational through short power failures, and provides time to save data and perform an orderly system shutdown in case of a prolonged blackout. The SU1000XLCD features a large internal battery set that provides 12.8 minutes of battery support for a half load (450 watts) and 3.8 minutes for a full load (900 watts). Intelligent battery management system extends battery life. During normal operation, incoming utility power keeps the UPS battery fully charged so that backup power will always be available if needed. For mission-critical applications demanding continuous uptime, the fully scalable SU1000XLCD can provide expandable runtime with optional external battery packs (Tripp Lite model [BP24V15RT2U](#), [BP24V28-2U](#) or [BP24V70-3U](#)), sold separately.

#### **High Power Factor and Highly Efficient Operation Reduces BTU Output**

The SU1000XLCD features a high 0.9 power factor and an optional, highly efficient economy mode setting that can significantly reduce a facility's energy costs. In economy mode, the UPS operates with 96% efficiency, minimizing heat output, reducing cooling requirements and consuming less electricity.

#### **AC Line and Tel/Ethernet Surge Suppression**

A sudden power surge or spike can damage or destroy electronic components and wipe out irreplaceable data. The SU1000XLCD features a 570-joule surge suppression rating to protect connected components and data from the harmful effects of power surges. One set of tel/Ethernet (RJ45) jacks provides surge protection for a standard phone or network connection (cable not included).

#### **EMI/RFI Line Noise Filtering**

Various electrical and radio sources can cause disruptive interference on the AC line. This line noise is a common cause of incremental hardware damage, data corruption and audio/video performance problems. The SU1000XLCD incorporates technology that filters out disruptive line noise, preventing it from affecting your equipment.

#### **LCD Screen and Audible Alarm**

The SU1000XLCD features a front-panel LCD screen that enables IT personnel to monitor line power, on-line mode, bypass mode, on-battery, overload, battery low, replace battery and fault status information. It is supplemented by an audible alarm that signals UPS startup, power failure, low battery, overload, UPS fault and remote shutdown conditions.

#### **USB/DB9 Ports, Network Management Cards and PowerAlert Software**

SU1000XLCD includes HID-compliant USB interface that enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. USB and DB9 ports enable data-saving unattended shutdown when used with Tripp Lite's PowerAlert software, available via FREE download from [www.tripplite.com/poweralert](http://www.tripplite.com/poweralert). Compatible with Tripp Lite UPS management card options [TLNETCARD](#), [WEBCARDLX](#), [SNMPWEBCARD](#), [MODBUSCARD](#) and [RELAYOCARD](#).

#### **Emergency Power Off (EPO) Capability**

The SU1000XLCD features an EPO interface port that supports emergency shutoff in large facilities (cable included).

#### **Peace of Mind**

The SU1000XLCD comes with \$250,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only) for connected equipment.

## **Specifications**



| OUTPUT  |  |
|---|--|
| Output Volt Amp Capacity (VA)                 | 1000   |
| Output kVA Capacity (kVA)                     | 1  |
| Output Watt Capacity (Watts)                  | 900  |
| Output kW Capacity (kW)                       | 0.9  |
| Output Capacity Details                       | <p>ON LINE MODE: Maximum output capacity rating is reduced to 810W at 100V nominal; FREQUENCY REGULATION / CONVERSION MODE: Maximum output ratings are reduced in frequency regulation / conversion mode (127/120/115/110V 630 watts / 100V 567 watts) OVERLOAD CAPACITY: Supports inverter operation up to 105% load continuously, 125% load for 3 minutes; 150% load for 30 seconds and &gt;150% load for 0.5 seconds before switching to BYPASS (when bypass input voltage and frequency are WITHIN bypass limits) or SHUTDOWN (when bypass input voltage or frequency are OUTSIDE bypass limits)</p>   |
| Power Factor                                  | 0.9  |
| Crest Factor                                  | 3:1  |
| Nominal Output Voltage(s) Supported           | 100V; 110V; 115V; 120V; 127V   |
| Nominal Voltage Details                       | 120V default   |
| Frequency Compatibility                       | 50 / 60 Hz; Supports 50 to 60 Hz and 60 to 50 Hz conversion  |
| Frequency Compatibility Details               | <p>ON LINE MODE: Output frequency is automatically configured to match nominal input frequency on startup; Output matches input frequency when +/-5Hz of nominal; Output is regulated to +/-0.05Hz when input frequency exceeds +/-5Hz of nominal. UPS switches to battery mode when input frequency is below 40Hz or above 70Hz.<br/>           FREQUENCY REGULATION / CONVERSION MODE: Output is regulated to +/-0.05Hz of selected output frequency when input is 40 to 70Hz; UPS switches to battery mode when input frequency is below 40Hz or above 70Hz.<br/>           BATTERY MODE: Output is regulated to +/-0.05Hz of selected nominal.</p> |
| Output Voltage Regulation (Line Mode)         | +/- 2%   |
| Output Voltage Regulation (Economy Line Mode) | +/- 10%  |
| Output Voltage Regulation (Battery Mode)      | +/- 3%   |
| Output Receptacles                            | (6) 5-15R  |
| Load Management Receptacles                   | Two switchable single-outlet 5-15R load banks  |
| Output AC Waveform (AC Mode)                  | Pure Sine wave   |
| Output AC Waveform (Battery Mode)             | Pure Sine wave   |
| INPUT   |  |
| Rated input current (Maximum Load)            | 10A  |
| Nominal Input Voltage(s) Supported            | 100V AC; 110V AC; 120V AC; 127V AC   |
| Nominal Input Voltage Description             | 120V factory default   |
| UPS Input Connection Type                     | 5-15P  |
| Input Circuit Breakers                        | 15A  |
| UPS Input Cord Length (ft.)                   | 10   |



|  |   |
|--|---|
| UPS Input Cord Length (m)                    | 3.0   |
| Recommended Electrical Service               | 15A 120V  |
| Input Phase                                  | Single-Phase  |
| <b>BATTERY</b>                               |   |
| Full Load Runtime (min.)                     | 3.8 min. (900w)   |
| Half Load Runtime (min.)                     | 12.8 min. (450w)  |
| Expandable Battery Runtime                   | Extended runtime supported via optional external battery packs  |
| External Battery Pack Compatibility          | BP24V15RT2U(limit 1); BP24V28-2U(limit 1); BP24V70-3U(multi-pack compatible)  |
| Expandable Runtime Description               | External battery configurations require the use of Tripp Lite's External Battery Configuration Software, see manual for details   |
| DC System Voltage (VDC)                      | 24  |
| Battery Recharge Rate (Included Batteries)   | Less than 3 hours from 10% to 90% (typical, full load discharge)  |
| Internal UPS Replacement Battery Cartridge   | RBC24V-LCD  |
| Battery Access                               | Battery access door   |
| Battery Replacement Description              | Hot-swappable, user replaceable batteries   |
| Expandable Runtime                           | Yes   |
| <b>VOLTAGE REGULATION</b>                    |   |
| Voltage Regulation Description               | Online, double-conversion power conditioning  |
| Overvoltage Correction                       | 2% output voltage regulation during overvoltages to 150   |
| Undervoltage Correction                      | 2% output voltage regulation during undervoltages to 55V (33% load), 70V (70% load), 100V (100% load)   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Front Panel LCD Display                      | Front panel LCD information and configuration screen offers detailed UPS and site power status and operating data, plus configuration of voltage, frequency, operating mode, alarm function and a variety of additional options |
| Switches                                     | 2 switches control off/on power status and alarm-cancel/self-test operation   |
| Alarm Cancel Operation                       | Power-fail alarm can be temporarily silenced using alarm-cancel switch; silent mode alarm configuration option available  |
| Audible Alarm                                | Audible alarm indicates UPS startup, power-failure, low-battery, overload, UPS fault and remote shutdown conditions   |
| <b>SURGE / NOISE SUPPRESSION</b>             |   |
| UPS AC Suppression Joule Rating              | 570   |
| UPS AC Suppression Response Time             | Instantaneous   |
| UPS Dataline Suppression                     | 1 line TEL/DSL (1 in / 1 out); 10/100Base T Ethernet  |
| EMI / RFI AC Noise Suppression               | Yes   |



| <b>PHYSICAL</b>                               |  |
|---|--|
| Primary Form Factor                           | Tower  |
| UPS Power Module Dimensions (hwd, in.)        | 10 x 6.8 x 13.2  |
| UPS Power Module Dimensions (hwd, cm)         | 25.40 x 17.27 x 33.53  |
| UPS Power Module Weight (lbs.)                | 28.7   |
| UPS Power Module Weight (kg)                  | 13.02  |
| UPS Shipping Dimensions (hwd / in.)           | 14.2 x 10 x 18.5   |
| UPS Shipping Dimensions (hwd / cm)            | 36.07 x 25.40 x 46.99  |
| Shipping Weight (lbs.)                        | 33.5   |
| Shipping Weight (kg)                          | 15.2   |
| Cooling Method                                | Fan  |
| UPS Housing Material                          | Steel  |
| Primary UPS Height (mm)                       | 254  |
| Primary UPS Width (mm)                        | 173  |
| Primary UPS Depth (mm)                        | 335  |
| Shipping Height (mm)                          | 361  |
| Shipping Width (mm)                           | 254  |
| Shipping Depth (mm)                           | 470  |
| <b>ENVIRONMENTAL</b>                          |  |
| Operating Temperature Range                   | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius  |
| Storage Temperature Range                     | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius   |
| Relative Humidity                             | 0 to 95%, non-condensing   |
| AC Mode BTU / Hr. (Full Load)                 | 341  |
| AC Economy Mode BTU / Hr. (Full Load)         | 128  |
| Battery Mode BTU / Hr. (Full Load)            | 585  |
| AC Mode Efficiency Rating (100% Load)         | 90%  |
| AC Economy Mode Efficiency Rating (100% Load) | 95%  |
| Audible Noise                                 | < 50 dB at front side 1m   |
| <b>COMMUNICATIONS</b>                         |  |
| Communications Interface                      | USB (HID enabled); DB9 Serial; Contact closure; EPO (emergency power off); Slot for SNMP/Web interface |



|   |  |
|---|--|
| Network Management Cards                                    | <a href="#">SNMPWEBCARD</a> ; <a href="#">TLNETCARD</a> ; <a href="#">WEBCARDLX</a> ; <a href="#">MODBUSCARD</a> ; <a href="#">RELAYIOCARD</a>   |
| Network Monitoring Port Description                         | Supports detailed monitoring of UPS and site power conditions; DB9 port supports RS232 and contact closure communications  |
| PowerAlert Software   | For local monitoring via the UPS's built-in communication ports, download PowerAlert Local software at <a href="http://www.tripplite.com/poweralert">http://www.tripplite.com/poweralert</a> |
| Communications Cable  | USB and DB9 cabling included   |
| WatchDog Compatibility                                      | Supports Watchdog application, OS and hard-reboot restart options for remote applications  |
| <b>LINE / BATTERY TRANSFER</b>                              |  |
| Transfer Time   | Zero transfer time (0 ms.) in online, double-conversion and frequency regulation / conversion modes;   |
| Low Voltage Transfer to Battery Power (Setpoint)            | 55V (33% load), 70V (70% load), 100V (100% load)   |
| High Voltage Transfer to Battery Power (Setpoint)           | 150  |
| <b>SPECIAL FEATURES</b>                                     |  |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported   |
| High Availability UPS Features                              | Automatic inverter bypass; Hot swappable batteries   |
| Green Energy-Saving Features                                | High efficiency economy mode operation; Individually controllable load banks; Schedulable daily hours of economy mode operation  |
| <b>CERTIFICATIONS</b>                                       |  |
| UPS Certifications  | Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category B (EMI)   |
| <b>WARRANTY</b>   |  |
| Product Warranty Period (Worldwide)                         | 2-year limited warranty  |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico)  | \$250,000 <a href="#">Ultimate Lifetime Insurance</a>  |

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>