

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

—, — .

© COPYRIGHT — By —

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P

LTR

DESCRIPTION

DATE

DWN

APVD

B

REVISED PER ECO-15-005333

07JUL2015

AP

RP

94,8

90,0

2,4

2,9 DIA

0,85

3,81

0,3

3,81

ROW Z
POS. 2

14,7

12,35

5,08

5,08

4,0

84,8

0,5

10,0

9,9

5,08

15 X 5,08 = 76,20

84,1

NOTES:

1

MATERIAL : — HOUSING : POLYESTER G.F.
COLOUR : GREY.
— CONTACTS : PHOSPHORBRONZE.

2

FINISH : —1: EIC 60603-2 PERFORMANCE LEVEL I OVER NICKEL
IN CONTACT AREA.
AT POST AREA 2,5µm Sn OVER 1,25µm NI.
—4: EIC 60603-2 PERFORMANCE LEVEL II OVER NICKEL
IN CONTACT AREA.
AT POST AREA 2,5µm Sn OVER 1,25µm NI.

3

FOR P.C.B.-THICKNESS 1,6-2,4

P.C.B. HOLE DIM. ACTION PIN

DRILLED HOLE : 1,15 ± 0,025 mm

FIN. HOLE : 0,94 to 1,09 mm

AFTER REFLOW : 0,91 to 1,09 mm

Cu-thks : 0,025 to 0,075 mm

SnPb-thks : 0,004 to 0,010 mm

ROW

z b d

32

30

28

26

24

22

20

18

16

14

12

10

8

6

4

2

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

POS

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

AN ASTERISK „X” DENOTES A CONTACT.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

0 PLC ± —

1 PLC ± —

2 PLC ± —

3 PLC ± —

4 PLC ± —

ANGLES ± —

FINISH —

DWN

J.GIBBELS

18OCT95

CHK

R.V.LOKVEN

APVD

—

PRODUCT SPEC

—

APPLICATION SPEC

—

WEIGHT

—

CUSTOMER DRAWING

FINISH

—

OBSOLETE

SEE NOTE 2

SEE NOTE 1

188826-4

188826-1

FINISH

MATERIAL

PARTNUMBER

STE

TE Connectivity

NAME

31 POS. TYPE F FEMALE
B.T.B. — A.P. CONNECTOR.

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-188826

—

SCALE

NTS

SHEET

1 OF 1

REV

B

1470-19 (3/11)