





States of America

SPECIFICATIONS

- Dissipative Low Charging Vinyl Badge Holder
 - Material Thickness: 0.012" (0.3 mm) front & 0.024" (0.6 mm) back
 - Material Tolerance (thickness): ±10%
 - Material Color: matte front & back
- Highly visible yellow header with ESD protective symbol
- Includes a 1/8" (3 mm) x 9/16" (14 mm) punch through slot, setback 3/8" (10 mm) from top
- 4" (101 mm) x 3-3/8" (86 mm) (Outer Dimension)
- Opening setback 3/4" (19 mm) from top with zipper closure
- Embossing with: Menda and Made In America along the bottom of the badge holder
- RS: 1 x 10⁶ < 1 x 10¹⁰ ohms per ANSI/ESD STM11.11
- Genuine Made In America accept no substitutes
- We can do customs just let us know your insert size

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors. replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." [ESD Handbook ESD TR20.20-2008 section 2.4 Sources of Static Electricitv1

Specifications and procedures subject to change without notice.

ESD BADGE HOLDER, HORIZONTAL, 3-3/8" X 2-3/8" INSERT SIZE, W/ YELLOW HEADER & ZIPPER CLOSURE

+/- 1/16" tolerances on dimensions unless specified

MADE IN

AMERICA

3651 WALNUT AVENUE, CHINO, CA 91710

PHONE: (909) 627-2453 WEBSITE: Menda-ID.com **DRAWING NUMBER** 35017

DATE April 2015

MENDA

Back