

## Cable sleeve - CES-STPG-GY-2X4 - 1410438

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Small, slotted cable sleeves suitable for two cables with a diameter of 3 ... 4 mm, material: SEBS

### Product Features



### Key commercial data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	8.0 GRM
Custom tariff number	85472000
Country of origin	Poland

### Technical data

#### Dimensions

External cable diameter	2x 3 mm ... 4 mm
Length	29.5 mm
Width	19.5 mm
Height	17 mm

#### Ambient conditions

Degree of protection	IP44
Ambient temperature (operation)	-40 °C ... 80 °C (static)

#### General

Material	SEBS
Inflammability class according to UL 94	V0
Color	gray

# Cable sleeve - CES-STPG-GY-2X4 - 1410438

## Classifications

### eCl@ss

eCl@ss 4.0	27081002
eCl@ss 4.1	27081002
eCl@ss 5.0	27081002
eCl@ss 5.1	27081002
eCl@ss 6.0	27081002
eCl@ss 7.0	27081002

### ETIM

ETIM 3.0	EC000879
ETIM 4.0	EC002498
ETIM 5.0	EC000451

### UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708
UNSPSC 11	39121708
UNSPSC 12.01	39121708
UNSPSC 13.2	39121708

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / cULus Recognized

---


#### Ex Approvals

---

#### Approvals submitted

---

### Approval details

UL Recognized 
---


## Cable sleeve - CES-STPG-GY-2X4 - 1410438

### Approvals



### Drawings

Dimensional drawing



Dimensional drawing