

## Pin strip - PST 1,3/ 4-5,0 L15,5 - 1708561

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The figure shows a 6-position version


Pin strip, nominal current: 12 A, number of positions: 4, pitch: 5 mm, color: black, contact surface: Tin, The maximum current depends on the plug used. The lower of the two current values apply for plug and pin strip. The pin strip is made of highly temperature resistant plastic and is thus suitable for the reflow process.

### Your advantages

- ✓ Suitable for wave and reflow soldering processes
- ✓ Optimum pin geometry for all COMBICON pin strip connectors



### Key Commercial Data

|              |   |
|--------------|---|
| Packing unit | 50 pc   |
| GTIN         | <br>4 055626 007816 |
| GTIN         | 4055626007816   |

### Technical data

#### Dimensions

|                          |          |
|--------------------------|----------|
| Pitch                    | 5 mm     |
| Dimension a              | 15 mm    |
| Height                   | 9.5 mm   |
| Length of the solder pin | 3.5 mm   |
| Pin dimensions           | ø 1.3 mm |

#### General

|                                  |              |
|----------------------------------|--------------|
| Range of articles                | PST 1,3/..-V |
| Rated voltage (III/3)            | 250 V        |
| Connection in acc. with standard | EN-VDE       |
| Nominal current I <sub>N</sub>   | 12 A         |
| Color                            | black        |
| Number of positions              | 4            |

## Pin strip - PST 1,3/ 4-5,0 L15,5 - 1708561

### Technical data

#### Standards and Regulations

|                                  |        |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
|----------------------------------|--------|

#### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Approvals

#### Approvals

---

Approvals

EAC

---

Ex Approvals

#### Approval details

|     |   |         |
|-----|---|---------|
| EAC |  | B.01742 |
|-----|---|---------|

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>