

Photovoltaic connector - PV-FT-CF-C-4-170-BU-SP - 1705004

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RoHS

Key Commercial Data

Packing unit	50 pc
Minimum order quantity	300 pc
GTIN	 4 046356 750769
GTIN	4046356750769


Technical data

Environmental Product Compliance


China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Dimensional drawing



Dimension x = cable length
c: panel thickness - plastic: 2 - 6 mm; metal: 2 - 5 mm

Photovoltaic connector - PV-FT-CF-C-4-170-BU-SP - 1705004

Approvals

Approvals

Approvals

TÜV Rheinland / VDE Zeichengenehmigung / EAC

Ex Approvals

Approval details

TÜV Rheinland	http://www.certipedia.com	R 60126961
Nominal voltage UN	1500 V	

VDE Zeichengenehmigung		http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx	40031807
Nominal voltage UN	1500 V		
Nominal current IN	40 A		
mm²/AWG/kcmil	4		

EAC		B.01742
-----	---	---------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>