# **XAPG19601**



#### Main

Range of product	Harmony XAP
Product or component type	Die-cast empty control station
Device short name	XAPG
Product destination	For Ø 30 mm control and signalling units
Number of cut-out	1 cut-out
Colour of base of enclosure	Grey RAL 7032
Colour of cover	Grey RAL 7032
Material	Zinc alloy
Cable entry	1 hole with blanking plug for cable gland with <= 0.55 in (14 mm) 1 hole without blanking plug for cable gland with <= 0.55 in (14 mm)
Product mounting	Flush mounting
IP degree of protection	IP65 conforming to IEC 60529 IP657 conforming to NF C 20-010

### Complementary

Number of vertical rows

#### **Environment**

protective treatment	TC	- S
ambient air temperature for storage	-40158 °F (-4070 °C)	
ambient air temperature for operation	-13158 °F (-2570 °C)	- 0
electrical shock protection class	Class I conforming to IEC 60536 Class I conforming to NF C 20-030	- \$1

### Offer Sustainability

WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
Nickel compounds, which is known to the State of California to cause cancer, and	Nickel compounds, which is known to the State of California to cause cancer, and	
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive harm. harm.		

## Contractual warranty

•		
Warranty period	18 months	

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov