

THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		LOC	DIST	REVISIONS					
© COPYRIGHT		ALL INTERNATIONAL RIGHTS RESERVED.		J	—	P	LTR	DESCRIPTION	DATE	DWN	APVD
							C5	REVISED PER ECR-17-018148	13DEC17	SC	BH

19.3
11.1
9.06
7.11
3.15
2.9
0.8
3.96 (PITCH)
TRADE MARK
CIRCUIT No. 2

2
3.9
5.55
3.11

断面 A-A (SECT)

3.96 (PITCH)

1. APPLICABLE CONTACT PART NUMBER;
REC CONTACT: 175152-□ (#20-#16AWG)
175151-□ (#26-#22AWG)

2. TO BE USED WITH THE CONTACT WHICH IS RATED 105°C MAX

3. MATERIAL: PA66, UL94 V-0, GWIT 775°C

MATING CONN. PART NUMBER 嵌合相手型番	TEMPERATURE RATING 定格温度	TYPE 種類	HOUSING COLOR 色	Pos. 極数	PART NUMBER 型番
1-176282-5	130°C MAX	△3	GREEN 緑	2	1-176271-5
1-176282-1	130°C MAX	△3	NATURAL 自然色		1-176271-1△2
176282-□ 176292-□	105°C MAX	PA66	BLACK 黒		176271-9
			BLUE 青		176271-6
			YELLOW 黄		176271-4
			RED 赤	176271-2	
			NATURAL 自然色		176271-1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M.SHINDO 08NOV1989		CHK Y.FUJITA 08NOV1989		APVD Y.FUJITA 08NOV1989		NAME AMP UNIVERSAL POWER CONN. 3.96mm PITCH PLUG HOUSING 2 Pos. (SGL ROW) AMP ユニバーサルパワーコネクタ 2極 3.96mmピッチ キャップハウジング	
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: ≤10 ±0.2 10<≤30 ±0.25 30< ±0.3	PRODUCT SPEC 108-5302		APPLICATION SPEC		SIZE A3		CAGE CODE 00779	
MATERIAL SEE TABLE	ANGLES FINISH ±3°	WEIGHT		CUSTOMER DRAWING		DRAWING NO C-176271		RESTRICTED TO —	
				SCALE NTS		SHEET 1 OF 1		REV C5	

1. 適用端子型番;
リセコンタクト: 175152-□ (#20-#16AWG)
175151-□ (#26-#22AWG)

2. 適用コンタクトの使用温度は最大105°C