

Product: 1152A ☑



Broadband Coax, Series 6, 18 AWG Solid BCCS, Quad Shield, FEP Jkt, CMP

Product Description

Broadband Coax, Series 6, 18 AWG Solid Bare Copper Covered Steel Conductor, FEP Insulation, Foil + 60% Tinned Copper Braid + Foil + 40% Tinned Copper Braid Shield, FEP Jacket, CMP

Technical Specifications

Product Overview

Suitable Applications: Broadband, Cable Television (CATV), RF drop cable, Over-The-Air (OTA) antennas	
Construction Details	
RG Type:	6
Series Type:	6

Conductor

AWG	Stranding	Nom. Diameter	Material
18	Solid	0.040 in	BCCS - Bare Copper Covered Steel

Insulation

Material	Nom. Diameter
FEP - Fluorinated Ethylene Propylene (Foam)	0.170

Outer Shield Material

Layer	Outer Shield Type	Material	Material Trade Name	Coverage
1	Таре	Tri-Laminate (Alum+Poly+Alum)	Duobond® II	100%
2	Braid	Tinned Copper (TC)		60%
3	Tape	Tri-Laminate (Alum+Poly+Alum)	Duofoil®	100%
4	Braid	Tinned Copper (TC)		40%

Outer Jacket Material

Material	Nom. Diameter
FEP - Fluorinated Ethylene Propylene	0.273 in

Electrical Characteristics

Return Loss (RL)

Frequency [MHz]	Min. Structural Return Loss [dB]
5 - 400 MHz	20 dB

Attenuation

Frequency	Nom. Attenuation [dB/100ft]
1 MHz	0.3 dB/100ft
10 MHz	0.66 dB/100ft
50 MHz	1.6 dB/100ft
100 MHz	2.2 dB/100ft
200 MHz	3.0 dB/100ft
400 MHz	4.6 dB/100ft

700 MHz	6.6 dB/100ft
900 MHz	7.7 dB/100ft
1000 MHz	8.2 dB/100ft

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Impedence	Nom. Velocity
28 Ohm/1000ft	1.8 Ohm/1000ft	16.5 pF/ft	75 Ohm	82%

Voltage

UL Voltage Rating 300 V (CMP)

Mechanical Characteristics

Temperature



Bend Radius

Installation	Min.
2.7 in	

Bulk Cable Weight:	45 lbs/1000ft	ĺ
Max. Pull Tension:	192 lbs	ı

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor, Outdoor, Burial
Sustainability:	CA Prop 65
Flammability / Fire Resistance:	NFPA 262
NEC / UL Compliance:	CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	ANSI/SCTE 74

Product Notes

Notes:	For use in indoor plenum environments but also suitable for outdoor and underground applications.

History

Update and Revision:	Revision Number: 0.324 Revision Date: 07-28-2020

© 2020 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.