



N = Number of poles
 Dim A = $N \times 5.08 + 0.25$
 Dim B = $(N - 1) \times 5.08$

SIGN	DATE	DESCRIPTION	APPROVER
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

- Material**
- Item ① Terminal screw: Steel, Zinc plating "-" slot type
 - Item ② Clamp: Brass, Ni plating
 - Item ③ Wire guard solder pin: Brass, Tin plated
 - Item ④ Terminal housing: Thermoplastic (UL94V-0)

- Electrical**
- Voltage rating: 300VAC
 - Current rating: 15A
 - Wire range:
 - Solid wire(AWG): 12-28
 - Stranded wire(AWG): 12-28
 - Torque(Lb-In): 4.3
 - Screw: M3
 - Wire strip length: 7-8mm
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -40°C to +115°C
 - Soldering temperature: 250°C ± 10°C / 5 Sec

PART NO.

YG xx 21 x 1 xxxx G

RoHS
Pb < 40,000ppm

No. of poles	0 Black (RAL9005)	0000 Standard @ Logo
02 2 Contacts	2 Red (RAL3001/D)	000A Standard ANY Logo
03 3 Contacts	3 Orange (RAL2011/P)	Any special item by customer request, please contact sales department.
— — — —	4 Yellow (RAL1018/A)	
24 24 Contacts	5 Green (RAL6018/T)	
	6 Blue (RAL5015/A)	
	8 Grey (RAL7035/D)	
	9 White (RAL1102)	
	C Green (RAL6018/U)	

SECTION P-P

ANYTEK		CUSTOMER COPY	
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD			
TITLE: YG 5.08mm Series 2P-24P (W/O cover)		DWG NO.: 8YG0001	
PART NO.: YGxx21x1xxxxG		CUST NO.:	
APPROVED	CHECKED	DESIGNED	DRAWN
		Aaron 2011.04.07	Jacke 08/11/21
		SHEET: 01/01	
		UNIT: mm	
		SCALE: 2:1	
		REV.: B	
		Tolerance	
		X. ±0.50	
		X.X ±0.30	
		X.XX ±0.10	
		X° ±1°	