

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

AJ

16

P

LTR

DESCRIPTION

DATE

DWN

APVD



A

REV PER 0514-0114-04




04-26-04

JDP


DPG

FOLD CENTER CONDUCTOR
BEFORE CRIMPING

BRAID STRIP LENGTH

OPTIONAL PROCEDURE
FOR GROUNDING
TERMINATION
SCALE 2:1

SECTION A-A



SECTION B-B


1. FOR USE WITH RG 58/U L CABLE.

2. FOR USE WITH .062 DIA. BOARD HOLE.

3 TIN-LEAD PLATE PER ASTM B-545

4 TIN PLATE PER ASTM B-545

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
INCHESTOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	$\pm -$
1 PLC	$\pm -$
2 PLC	$\pm -$
3 PLC	$\pm .008$
4 PLC	$\pm -$
ANGLES	$\pm -$
FINISH	$\pm -$

MATERIAL
BRASS, ASTM B 36

DWN

T. SMITH

10-04-83

CHK

C.F.

10-04-85

APVD

R.K.

10-04-85

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

Tyco Electronics Corporation
Harrisburg, PA 17105-3608

NAME

COAXIAL PCB TERMINAL,
PICK CRIMP TYPE
BRAID-PIC

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-226854

SCALE 5:1

SHEET 1 OF 1

REV A

4	9-226854-0
3	226854-1
FINISH	PART NUMBER