



| PART NUMBER | SSL-LX30FT14IGW                     | REV. | B    |
|-------------|-------------------------------------|------|------|
| DATE        | E.C.N. NUMBER AND REVISION COMMENTS |      | REV. |
| 4.20.01     | E.C.N. #10BRDR. & REDRAWN IN 3D.    |      | A    |
| 07.12.12    | E.C.N. #10BRDR. & REDRAWN.          |      | B    |



| ELECTRO-OPTICAL CHARACTERISTICS Ta=25°C If=20mA |                          |         |         |          |           |
|-------------------------------------------------|--------------------------|---------|---------|----------|-----------|
| PARAMETER                                       | MIN                      | TYP     | MAX     | UNITS    | TEST COND |
| PEAK WAVELENGTH (R/G)                           |                          | 635/565 |         | nm       |           |
| FORWARD VOLTAGE (R/G)                           |                          | 2.0/2.2 | 2.5/2.6 | Vf       |           |
| REVERSE VOLTAGE                                 | 5.0                      |         |         | Vr       | Ir=100μA  |
| AXIAL INTENSITY                                 |                          | 5       |         | mcd      | If=20mA   |
| VIEWING ANGLE                                   |                          | 100     |         | 2x theta |           |
| EMITTED COLOR:                                  | RED/GREEN                |         |         |          |           |
| LENS FINISH:                                    | MILKY WHITE TOP DIFFUSED |         |         |          |           |

## LIMITS OF SAFE OPERATION AT 25°C

| PARAMETER             | MAX        | UNITS |
|-----------------------|------------|-------|
| PEAK FORWARD CURRENT* | 150        | mA    |
| STEADY CURRENT (R/G)  | 30/25      | mA    |
| POWER DISSIPATION     | 105        | mW    |
| DERATE FROM 25°C      | -1.6       | mW/°C |
| OPERATING TEMP.       | -40 TO +85 | °C    |
| STORAGE TEMP.         | -40 TO +85 | °C    |
| SOLDERING TEMP.       | +260       | °C    |
| 2.0mm FROM BODY       | 3          | SEC.  |

\* t&lt;10μs

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= <sup>+DECIMAL PRECISION</sup><sub>-0.00</sub> MAX.= <sup>+0.00</sup><sub>-DECIMAL PRECISION</sub>

UNCONTROLLED DOCUMENT

## QUASAR BRITE T-3mm (T-1) FLAT TOP RED/GREEN BI-COLOR LED.

\*\*THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.\*\*

## CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

|        |           |           |    |
|--------|-----------|-----------|----|
| DATE:  | 07.10.12  | DRAWN BY: | AB |
| PAGE:  | 1 OF 1    | CHKD BY:  | KF |
| SCALE: | NTS       | APRVD BY: | KF |
| UNIT:  | mm [INCH] |           | Ⓟ  |