

ROHS COMPLIANT

PRODUCT DATA DRAWING

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
-	NRN 42983	04/19	GPF

MATERIAL:

CONNECTORS:

CABLE:

SHRINK TUBING:

SMMP JACK (3221-40007)

SMA PLUG (SF2911-60172)

FLEXIBLE Ø.047 CABLE

M23053/5

SV P/N	OAL
7032-7524	6.000
7032-7525	12.000


PERFORMANCE:

IMPEDANCE:

FREQ. RANGE:

50 OHMS

DC TO 18.0 GHz

MATERIAL:	SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES:	UNLESS OTHERWISE SPECIFIED 1) ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES .005 R. MAX. 4) CHAM. 1ST & LAST THREADS. 5) SURFACE ROUGHNESS 63. MIL-STD-10. 6) DIA.'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R. 7) REMOVE ALL BURRS	 2400 Centrepark West Drive, Suite 100 West Palm Beach, FL 33409 TITLE: SMMP JACK TO SMA PLUG FOR FLEXIBLE Ø.047 CABLE ASSEMBLY <table><tr><td>SIZE</td><td>CAGE CODE</td><td>DWG. NO.</td></tr><tr><td>B</td><td>95077</td><td>7032-7524-7525</td></tr></table> <table><tr><td>SCALE: 2:1</td><td>SHEET 1 OF 1</td></tr></table>	SIZE	CAGE CODE	DWG. NO.	B	95077	7032-7524-7525	SCALE: 2:1	SHEET 1 OF 1
SIZE	CAGE CODE	DWG. NO.										
B	95077	7032-7524-7525										
SCALE: 2:1	SHEET 1 OF 1											
FINISH:	SEE NOTES	FRACTIONAL: ±1/64 ANGULAR: X° ±1°0' X°X' ±15'										
SURFACE AREA:	N/A	DECIMAL: .X ±.030 .XX ±.010 .XXX ±.005										
PROPRIETARY THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SV MICROWAVE, INC IS PROHIBITED.		INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994										
THIRD ANGLE PROJECTION		DRAWN: SJ 04/01/19										
		CHECKED: GPF 04/01/19										
		APPROVED: GPF 04/01/19										