Product datasheet Characteristics

9007ML01S0055

NЛ	Oin
IVI	аш
	•

Device application	Machine tools	
	Earth moving equipment	
	General transportation	
Device short name	ML	

Complementary

Line Rated Current	10 A
Body material	Cast zinc
Cable length	0 m
Contacts material	Silver alloy (Ag/Ni)
Contact operation	Snap action
Mounting support	Shoulder
Operating force	80 ozf
Permissible voltage	<= 28 V DC
Switch actuation	Vertical
Connector type	Male micro 5 pins
Type of operator	Spring return push rod plunger

Environment

ambient air temperature for operation	-4221 °F	
IP degree of protection	IP67	
NEMA degree of protection	NEMA 1/2/4/6/6P/12/13	
product certifications	CE CSA UL listed	
shock resistance	35 gn	
vibration resistance	10 gn 751200 Hz	

Offer Sustainability

Not Green Premium product	Not Green Premium product
Will not be Compliant	Will not be Compliant
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Stat of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov