## Product datasheet Characteristics

# 9007ML01S0055

#### Main

Device application	Machine tools Earth moving equipment General transportation
Device short name	ML

## Complementary

Line Rated Current	10 A
Body material	Cast zinc
Cable length	0 m
Contacts material	Silver alloy (Ag/Ni)
Contact operation	Snap action
Mounting support	Shoulder
Operating force	80 ozf
Permissible voltage	<= 28 V DC
Switch actuation	Vertical
Connector type	Male micro 5 pins
Type of operator	Spring return push rod plunger

## Environment

ambient air temperature for operation	-4221 °F
IP degree of protection	IP67
NEMA degree of protection	NEMA 1/2/4/6/6P/12/13
product certifications	CE CSA UL listed
shock resistance	35 gn
vibration resistance	10 gn 751200 Hz

### **Offer Sustainability**

Not Green Premium product	Not Green Premium product
Will not be Compliant	Will not be Compliant
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the Stat of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Star of California to cause birth defects or other reproductive harm.	teDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

