XZCPA0941L5



Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	Application

Complementary

Electrical connection	M8, 4 pins straight female connector	
Cable connector fixing	Screw-on	
Collar material	Stainless steel 316L	_
Status LED	Without	_
Cable length	16.4 ft (5 m)	_
Cable outer diameter	0.21 in (5.3 mm)	
Cable composition	4 x 0.34 mm²	
Wire insulation material	PVC	
System Voltage	75 V DC	
Line Rated Current	4 A	_
Contact resistance	5000 μOhm	_
Insulating resistance	1 GΩ	
Product weight	0.88 lb(US) (0.4 kg)	_

Environment

IP degree of protection	IP68	
ambient air temperature for operation	-13185 °F (-2585 °C) (static)	
ambient air temperature for storage	-31212 °F (-35100 °C)	

Not Green Premium product

Offer Sustainability


Not Green Premium product

Compliant - since 0601 - Schneider Electric declaration of conformity	Compliant - since 0601 - Schneider Electric declaration of conformity	
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm.		
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov	

Contractual warranty

Warranty period	18 months


Dimensions



L: Lenght of cable

Connections and Schemes

Connector



BN: Brown
BK: Black
BU: Blue
WH: White