



Heyco® Rubber Grommets

For Panels .063" (1,6 mm) Thick

- **Used to protect through holes.** Help eliminate sharp edges so your wires are protected and add aesthetic value to your application.
- 115 sizes available that will accommodate mounting holes ranging from .250" (6,4 mm) to holes as large as 2.375" (60,3 mm) diameter and panel thicknesses from .063" (1,6 mm) to .188" (4,8 mm).
- Rubber grommets are constructed of SBR (unless otherwise noted) with an operating temperature range of -40°F (-40°C) to 221°F (105°C).
- SBR grommets have good water resistant characteristics and are suitable for most moderate chemicals and wet or dry organic acids.
- Provide vibration dampening.

| MOUNTING HOLE DIAMETER | PART NO. | DESCRIPTION | MATERIAL | PART DIMENSIONS | | | | | |
|------------------------|----------|-------------|----------|-------------------|-----------|-----------------|-----------|------------------|--|
| | | | | A Inside Diameter | | B Head Diameter | | C Overall Height | |
| in. mm. | Black | | | in. mm. | in. mm. | in. mm. | in. mm. | in. mm. | |

For .063" (1,6 mm) Thick Panels

| | | | | | | | | | | |
|-------|------|-------|--------------|----------|------|------|------|------|-----|------|
| .250 | 6,4 | G1004 | RG 250-4-2 | SBR | .13 | 3,2 | .34 | 8,7 | .19 | 4,8 |
| | | G1005 | RG 250-5-2 | SBR | .16 | 4,0 | .38 | 9,5 | | |
| | | G1006 | RG 250-5-2A | SBR | .16 | 4,0 | .44 | 11,1 | .38 | 9,5 |
| .312 | 7,9 | G1017 | RG 312-6-2 | SBR | .19 | 4,8 | .41 | 10,3 | .22 | 5,6 |
| | | G1018 | RG 312-6-2A | Nitrile | .19 | 4,8 | .44 | 11,1 | .19 | 4,8 |
| | | G1019 | RG 312-6-2B | SBR | .19 | 4,8 | .50 | 12,7 | .25 | 6,4 |
| | | G1026 | RG 312-7-2 | SBR | .22 | 5,6 | .44 | 11,1 | .19 | 4,8 |
| .375 | 9,5 | G1037 | RG 375-8-2 | EPDM | .25 | 6,4 | .56 | 14,3 | .25 | 6,4 |
| | | G1042 | RG 375-9-2 | SBR | .28 | 7,1 | | | | |
| .437 | 11,1 | G1052 | RG 437-8-2 | SBR | .25 | 6,4 | .63 | 15,9 | .19 | 4,8 |
| | | G1053 | RG 437-8-2A | Isoprene | .25 | 6,4 | .63 | 15,9 | .31 | 8,0 |
| | | G1061 | RG 437-10-2 | SBR | .31 | 8,0 | .63 | 15,9 | .28 | 7,1 |
| .500 | 12,7 | G1089 | RG 500-12-2 | SBR | .38 | 9,5 | .63 | 15,9 | .25 | 6,4 |
| | | G1090 | RG 500-12-2A | SBR | .38 | 9,5 | .69 | 17,5 | .28 | 7,1 |
| .562 | 14,3 | G1112 | RG 562-10-2 | SBR | .31 | 8,0 | .81 | 20,7 | .31 | 8,0 |
| | | G1123 | RG 562-14-2 | SBR | .44 | 11,1 | .75 | 19,1 | .25 | 6,4 |
| .625 | 15,9 | G1130 | RG 625-12-2 | SBR | .38 | 9,5 | .88 | 22,2 | .31 | 8,0 |
| | | G1137 | RG 625-16-2 | SBR | .50 | 12,7 | .81 | 20,7 | .28 | 7,1 |
| .687 | 17,5 | G1150 | RG 687-14-2 | SBR | .44 | 11,1 | .94 | 23,8 | .31 | 8,0 |
| | | G1151 | RG 687-14-2A | SBR | .44 | 11,1 | .94 | 23,8 | .35 | 8,8 |
| | | G1155 | RG 687-16-2 | SBR | .50 | 12,7 | .88 | 22,2 | .25 | 6,4 |
| .750 | 19,1 | G1174 | RG 750-12-2 | SBR | .38 | 9,5 | 1.00 | 25,4 | .38 | 9,5 |
| | | G1176 | RG 750-16-2 | SBR | .50 | 12,7 | .88 | 22,2 | | |
| | | G1177 | RG 750-16-2A | SBR | .50 | 12,7 | 1.00 | 25,4 | .25 | 6,4 |
| .812 | 20,6 | G1192 | RG 812-16-2 | SBR | .50 | 12,7 | | | | |
| | | G1197 | RG 812-18-2 | SBR | .56 | 14,3 | 1.06 | 27,0 | .31 | 8,0 |
| .875 | 22,2 | G1208 | RG 875-10-2 | SBR | .31 | 8,0 | 1.38 | 34,9 | .25 | 6,4 |
| | | G1215 | RG 875-20-2 | SBR | .63 | 15,9 | 1.13 | 28,6 | .31 | 8,0 |
| 1.000 | 25,4 | G1242 | RG 1000-12-2 | SBR | .38 | 9,5 | 1.25 | 31,8 | .25 | 6,4 |
| | | G1246 | RG 1000-16-2 | SBR | .50 | 12,7 | | | | |
| | | G1252 | RG 1000-22-2 | SBR | .69 | 17,5 | 1.31 | 33,4 | .38 | 9,5 |
| 1.062 | 27,0 | G1258 | RG 1000-24-2 | SBR | .75 | 19,1 | 1.25 | 31,8 | .30 | 7,5 |
| | | G1269 | RG 1062-24-2 | SBR | .75 | 19,1 | 1.38 | 34,9 | .38 | 9,5 |
| 1.250 | 31,8 | G1290 | RG 1250-16-2 | SBR | .50 | 12,7 | | | | |
| | | G1294 | RG 1250-20-2 | SBR | .63 | 15,9 | 1.50 | 38,1 | .25 | 6,4 |
| | | G1298 | RG 1250-24-2 | SBR | .75 | 19,1 | 1.63 | 41,3 | | |
| | | G1303 | RG 1250-28-2 | SBR | .88 | 22,2 | 1.63 | 41,3 | .44 | 11,1 |
| 1.375 | 34,9 | G1311 | RG 1250-32-2 | SBR | 1.00 | 25,4 | 1.56 | 39,7 | .31 | 8,0 |
| | | G1320 | RG 1375-32-2 | SBR | 1.00 | 25,4 | 1.75 | 44,5 | .44 | 11,1 |
| 1.500 | 38,1 | G1347 | RG 1500-36-2 | SBR | 1.13 | 28,6 | 1.88 | 47,6 | .38 | 9,5 |
| | | G1349 | RG 1500-40-2 | Nitrile | 1.25 | 31,8 | 1.88 | 47,6 | .34 | 8,7 |

Standard color black.



Quick Specs

Material
Temperature Range

SBR, Nitrile, EPDM, or Isoprene
-40°F (-40°C) to 221°F (105°C)