







Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du proprietaire. Propriete de c FCI. Droits de reproduction FCI.

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.



LAY-OUT
P.C.B.- HOLE



PERFORMANCE CHARACTERISTICS

CURRENT RATING 1.5A AT 20°C (FULLY LOADED)
1 A AT 70°C (FULLY LOADED)

RATED VOLTAGE : 500 V AC (CONT /CONT)

OPERATING TEMPERATURE : -55°C TO 125°C

CONTACT RESISTANCE 20 MΩ MAX

INSERTION FORCE : 0.75N MAX/CONT

EXTRACTION FORCE : 0.15N MIN/CONT

INSULATION RESISTANCE : 10⁴ MΩ MIN

1. HM2R30PA5100
- LEAD FREE INDICATOR : LF=LEAD FREE(DIGIT 15&16)
- PLATING CODE(DIGIT 13&14)

Plating code	Plating	Performance Level
AA	0.75µm Au	IEC performance level 2(250mating cycles)orTELCORDIA C0
AB	1.25µm Au	TELCORDIA UE

2. THIS PRODUCT IS CSA APPROVED.
THIS PRODUCT IS UL RECOGNIZED.
3. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING :
BS.A.201572.001
4. THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND
OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

rev	ecn no	dr	date
A	DG09-0243	NZ	Jul-20-2009
B	DG10-0093	NZ	Mar-08-2010
C	DG10-0110	NZ	Jun-08-2010
-	-	-	-
-	-	-	-

Material				Spec ref								
Mat code				✓	tolerance 1DEC ± 0.2 1DEC 2DEC ± 0.1 2DEC ANGLES ± 1° HOEKEN	projection 	MM 					
Heattreat												
Plating/Finish												
Dr	Nickor Zuo	Jul-20-09					size	A4	Scale	2.000		
Eng	Nickor Zuo	Jul-20-09	Product family				MILLIPACS					
Chr	PeiMing Zheng	Jul-20-09	Model Name				ECN					
Appr	Joseph Hsia	Jul-20-09	Model Revision				REL Level					
		title				MPACS 5+2R RA RCP CONN TYPE C				dwg no	BSC201418020	Rev. C
Pro/E file		catalog no		HM2R30PA5100----		CUSTOMER DRAWING				sheet 1 of 1		