



注記
NOTES

- 各部の反りは0.5最大。
WARPING : 0.5 MAX.
- サーキットNO.はNO."1"のみ表示。
CIRCUIT NO. : 1 ONLY.

| | | | | |
|-------|------|------------|--------------|--------------------|
| 30.4 | 25.4 | 39-01-1060 | 5197-063 | 6 |
| 10.08 | 5.08 | 39-01-1020 | 5197-023 | 2 |
| B | A | EDP NO. | MATERIAL NO. | 極数 NO. OF CXTS. |
| | | | MODEL NO. | 5197-N3 |

| | | | | | | |
|----------------------------------------------------------------------------------------------------------------------------|---------------------------------------|--------------|-----------------|-------------------------------------------------------------------------------------------------------------------------------|------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| REVISED EC NO. J2009-0049 DRWN:NAKAMURA 2008/07/23 CHKD:T. HIRUYAMA 2008/07/23 APPR:NUKITA 2008/11/14 REV C | GENERAL TOLERANCES (UNLESS SPECIFIED) | | DIMENSION STYLE | SCALE | DESIGN UNITS | THIRD ANGLE PROJECTION SPOX 5.08 PITCH RECEPTACLE HOUSING MOLEX INCORPORATED SD-5197-001 SHEET NO. 1 OF 1 |
| | 10 UNDER ± 0.2 | | MM ONLY | 4:1 | METRIC | |
| | 10 OVER 30 UNDER ± 0.25 | | DRAWN BY | DATE | TITLE | |
| | 30 OVER ± 0.3 | | T. ASAKAWA | '95/5/9 | SPOX 5.08 PITCH RECEPTACLE HOUSING | |
| ANGULAR ± 3 ° | | CHECKED BY | DATE | MOLEX INCORPORATED | | |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | H. HIRAMOTO | '95/5/9 | DOCUMENT NO. | | |
| | | APPROVED BY | DATE | SEE TABLE | | |
| | | M. FUKUSHIMA | '95/5/9 | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | |
| | | MATERIAL NO. | | | | |

材料 MATERIAL
 ナイロン66, UL94V-0
 NYLON66, UL94V-0