

Technical drawing of the top view of a circular component. The drawing includes the following dimensions and labels:

- Overall width: 42.5 ± 0.3
- Overall height: 42.5 ± 0.3
- Top horizontal distance from left edge to center: 21.25 ± 0.15 (labeled as 21.25 ± 0.15 in the image)
- Top horizontal distance from center to right edge: 21.25 ± 0.15 (labeled as 21.25 ± 0.15 in the image)
- Top horizontal distance from left edge to first internal feature: 2 ± 0.2
- Top horizontal distance between first and second internal features: 22 ± 0.2
- Top horizontal distance from second internal feature to right edge: 2 ± 0.2
- Top vertical distance from top edge to first internal feature: 2.4 ± 0.1
- Top vertical distance between first and second internal features: 2
- Top vertical distance from second internal feature to top edge: 2.4 ± 0.1
- Bottom horizontal distance from left edge to center: 21.25 ± 0.15 (labeled as 21.25 ± 0.15 in the image)
- Bottom horizontal distance from center to right edge: 21.25 ± 0.15 (labeled as 21.25 ± 0.15 in the image)
- Bottom horizontal distance from left edge to first internal feature: 2 ± 0.2
- Bottom horizontal distance between first and second internal features: 4.5 ± 0.2
- Bottom horizontal distance from second internal feature to right edge: 2 ± 0.2
- Bottom vertical distance from bottom edge to first internal feature: 2 ± 0.2
- Bottom vertical distance between first and second internal features: 2
- Bottom vertical distance from second internal feature to bottom edge: 2 ± 0.2
- Overall width of the bottom section: 39.6 ± 0.3
- Label: 703 Silicon Glue Black

Technical drawing of a mechanical part (Fig. 1) showing a cross-section with dimensions: 16.1 ± 0.3 , 11.3 , 0.7 ± 0.1 , 4.75 ± 0.2 , 6 ± 0.2 , and a hole diameter of $\text{Ø}37.5 \pm 0.3$.

Specifications			Notes	Revision History					
Description	Value	Unit		Version	Description		Date	Approved	
Shape	Rectangle		1) All dimensions are in mm unless otherwise noted 2) All parts meet RoHS	1	Released from Engineering		2/8/2014	J.S.	
Resonant Frequency	600	(Hz)							
Frequency Range	600 ~ 5,000	(Hz)							
SPL @ 10cm	93	(dBA)							
Impedance	8	(Ohm)							
Cone Material	Polyetherimide								
Nominal Power	1.0	(W)							
Max Power	1.5	(W)							
Mount Type	Thru Hole								
Operating Temperature	-40 ~ +85	°C							
Storage Temperature	-40 ~ +85	°C	 DB UNLIMITED	Drawn by	Date	Checked by	Date	Approved by	Date
Weight	9	(g)		G.W.	1/27/2014	C.E.	2/5/2014	J.S.	2/8/2014
				High Temp Dynamic Speaker			SM420608-1		