



MECHANICAL DATA



SO8 PACKAGE

- PIN 1 – SOURCE
- PIN 2 – DRAIN
- PIN 3 – DRAIN
- PIN 4 – SOURCE
- PIN 5 – SOURCE
- PIN 6 – GATE
- PIN 7 – GATE
- PIN 8 – SOURCE

Dim.	mm	Tol.	Inches	Tol.
A	4.06	±0.08	0.160	±0.003
B	5.08	±0.08	0.200	±0.003
C	1.27	±0.08	0.050	±0.003
D	0.51	±0.08	0.020	±0.003
E	3.56	±0.08	0.140	±0.003
F	4.06	±0.08	0.160	±0.003
G	1.65	±0.08	0.065	±0.003
H	0.76	+0.25 -0.00	0.030	+0.010 -0.000
J	0.51	Min.	0.020	Min.
	1.02	Max.	0.040	Max.
K	45°	Max.	45°	Max.
	0°	Min.	0°	Min.
L	7°	Max.	7°	Max.
	0°	Min.	0°	Min.
M	0.20	±0.08	0.008	±0.003
N	2.18	Max.	0.086	Max.
P	4.57	±0.08	0.180	±0.003

**GOLD METALLISED
MULTI-PURPOSE SILICON
DMOS RF FET
5W – 28V – 1GHz
SINGLE ENDED**

FEATURES

- SIMPLIFIED AMPLIFIER DESIGN
- SUITABLE FOR BROAD BAND APPLICATIONS
- VERY LOW C_{rss}
- SIMPLE BIAS CIRCUITS
- LOW NOISE
- HIGH GAIN – 13 dB MINIMUM

APPLICATIONS

- HF/VHF/UHF COMMUNICATIONS
from 1 MHz to 1 GHz

ABSOLUTE MAXIMUM RATINGS ($T_{case} = 25^{\circ}C$ unless otherwise stated)

P_D	Power Dissipation	30W
BV_{DSS}	Drain – Source Breakdown Voltage *	65V
BV_{GSS}	Gate – Source Breakdown Voltage*	±20V
$I_{D(sat)}$	Drain Current	2A
T_{stg}	Storage Temperature	-65 to 150°C
T_j	Maximum Operating Junction Temperature	200°C

ELECTRICAL CHARACTERISTICS ($T_{\text{case}} = 25^{\circ}\text{C}$ unless otherwise stated)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
BV_{DSS} Drain–Source Breakdown Voltage	$V_{\text{GS}} = 0$ $I_{\text{D}} = 10\text{mA}$	65			V
I_{DSS} Zero Gate Voltage Drain Current	$V_{\text{DS}} = 28\text{V}$ $V_{\text{GS}} = 0$			2	mA
I_{GSS} Gate Leakage Current	$V_{\text{GS}} = 20\text{V}$ $V_{\text{DS}} = 0$			1	μA
$V_{\text{GS(th)}}$ Gate Threshold Voltage*	$I_{\text{D}} = 10\text{mA}$ $V_{\text{DS}} = V_{\text{GS}}$	1		5	V
g_{fs} Forward Transconductance*	$V_{\text{DS}} = 10\text{V}$ $I_{\text{D}} = 0.4\text{A}$	0.36			S
G_{PS} Common Source Power Gain	$P_{\text{O}} = 5\text{W}$	13			dB
η Drain Efficiency	$V_{\text{DS}} = 28\text{V}$ $I_{\text{DQ}} = 0.4\text{A}$	40			%
VSWR Load Mismatch Tolerance	$f = 1\text{GHz}$	20:1			—
C_{iss} Input Capacitance	$V_{\text{DS}} = 0\text{V}$ $V_{\text{GS}} = -5\text{V}$ $f = 1\text{MHz}$			24	pF
C_{oss} Output Capacitance	$V_{\text{DS}} = 28\text{V}$ $V_{\text{GS}} = 0$ $f = 1\text{MHz}$			12	pF
C_{rss} Reverse Transfer Capacitance	$V_{\text{DS}} = 28\text{V}$ $V_{\text{GS}} = 0$ $f = 1\text{MHz}$			1	pF

* Pulse Test: Pulse Duration = 300 μs , Duty Cycle $\leq 2\%$

THERMAL DATA

$R_{\text{THj-case}}$	Thermal Resistance Junction – Case	Max. 6°C / W
-----------------------	------------------------------------	--------------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TT Electronics:](#)

[D2020UK](#)