



HEYlock™ Locking IEC Power Cords

Universal C13 to C14 Locking Power Cords - designed for retrofit!
UL Listed (UL 817) and CE Compliant (IEC 60320)

- The only locking IEC 13-14 power cord that locks at both ends.
- Designed for retrofit - plug and play replacement for existing power cords.
- Universally compatible - requires no mating plug or receptacle on the other side of the connection.
- Consult Heyco for IEC 19-20 power cord configurations.

| Type | WIRE Gauge AWG/ Cond | Color * | Length * | | PART NO. | DESCRIPTION |
|------|-------------------------------|------------|-------------|-----|--------------|------------------------------|
| | | | Feet | M | | |
| H05 | 17/3 | Black | 1.7 | 0.5 | S8000 | LPC-C13/C14-17/3-BLK-H05-1.7 |
| | | | 3.3 | 1.0 | S8002 | LPC-C13/C14-17/3-BLK-H05-3.3 |
| | | | 5.0 | 1.5 | S8004 | LPC-C13/C14-17/3-BLK-H05-5.0 |
| | | | 6.6 | 2.0 | S8006 | LPC-C13/C14-17/3-BLK-H05-6.6 |
| | | | 8.3 | 2.5 | S8008 | LPC-C13/C14-17/3-BLK-H05-8.3 |
| SJT | 16/3 | Black | 1.7 | 0.5 | S8020 | LPC-C13/C14-16/3-BLK-SJT-1.7 |
| | | | 3.3 | 1.0 | S8022 | LPC-C13/C14-16/3-BLK-SJT-3.3 |
| | | | 5.0 | 1.5 | S8024 | LPC-C13/C14-16/3-BLK-SJT-5.0 |
| | | | 6.6 | 2.0 | S8026 | LPC-C13/C14-16/3-BLK-SJT-6.6 |
| SJT | 14/3 | Black | 1.7 | 0.5 | S8030 | LPC-C13/C14-14/3-BLK-SJT-1.7 |
| | | | 3.3 | 1.0 | S8032 | LPC-C13/C14-14/3-BLK-SJT-3.3 |
| | | | 5.0 | 1.5 | S8034 | LPC-C13/C14-14/3-BLK-SJT-5.0 |
| | | | 6.6 | 2.0 | S8036 | LPC-C13/C14-14/3-BLK-SJT-6.6 |

*Custom colors and lengths available, consult Heyco.



Universal C13 to 5-15P Locking Power Cords - designed for retrofit!

UL Listed (UL 817) and CE Compliant (IEC 60320)

- IEC 13 to NEMA 5-15P power cord that locks at the application end.
- Designed for retrofit - plug and play replacement for existing power cords.
- Universally compatible - requires no mating receptacle on the other side of the connection.
- IEC 13 to any International plug configuration available. Consult Heyco.

| Type | WIRE Gauge AWG/ Cond | Color * | Length * | | PART NO. | DESCRIPTION |
|------|-------------------------------|------------|-------------|-----|--------------|-------------------------------|
| | | | Feet | M | | |
| SJT | 18/3 | Black | 2.0 | 0.6 | S8052 | LPC-C13/515P-18/3-BLK-SJT-2.0 |
| | | | 3.0 | 0.9 | S8053 | LPC-C13/515P-18/3-BLK-SJT-3.0 |
| | | | 6.0 | 1.8 | S8056 | LPC-C13/515P-18/3-BLK-SJT-6.0 |
| SJT | 16/3 | Black | 2.0 | 0.6 | S8062 | LPC-C13/515P-16/3-BLK-SJT-2.0 |
| | | | 3.0 | 0.9 | S8063 | LPC-C13/515P-16/3-BLK-SJT-3.0 |
| | | | 6.0 | 1.8 | S8066 | LPC-C13/515P-16/3-BLK-SJT-6.0 |
| SJT | 14/3 | Black | 2.0 | 0.6 | S8072 | LPC-C13/515P-14/3-BLK-SJT-2.0 |
| | | | 3.0 | 0.9 | S8073 | LPC-C13/515P-14/3-BLK-SJT-3.0 |
| | | | 6.0 | 1.8 | S8076 | LPC-C13/515P-14/3-BLK-SJT-6.0 |

*Custom colors and lengths available, consult Heyco.

*Quick
Specs*

Materials Nylon 6/6 and PVC with Plated Copper Alloy Contacts
 Certifications Certified by UL for Compliance with both Canadian and U.S. Requirements under File E471200 (C13/C14)
 Certified by UL for Compliance with both Canadian and U.S. Requirements under File E115330 (C13/5-15P)