



REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	B3	REVISED PER ECO-15-010004	13JUL2015	NK	MZ
	C	REVISED PER ECO-17-004650	06APR2017	BDA	MZ



ALIGNMENT DOT, COLOR-WHITE

POSITIVE LOCK
INDICATOR

ALIGNMENT INDICATOR SLOTS



SECTION Z-Z



OBSOLETE	RED	NATURAL	Ø1.5	115°	1445534-05
OBSOLETE	BLACK	YELLOW	Ø0.75	130°	1445534-04
	BLACK	NATURAL	Ø1.5	115°	1445534-03
OBSOLETE	BLACK	NATURAL	Ø1.5	130°	1445534-02
	BLACK	YELLOW	Ø0.75	115°	1445534-01
	HOUSING COLOR	SEAL, WIRE ENTRY COLOR	ØX REF	K REF	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. WIEST 07MAY2001	TE Connectivity		
DIMENSIONS:		CHK G. DOUITY 07MAY2001			
mm		APVD H. WAKEEM 12JUN2003	NAME ASSEMBLY, PLUG, SIZE 8, 3 POSITION, SEALED, MINI CPC		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC	SIZE		
0 PLC ±0.5		APPLICATION SPEC	CAGE CODE		
1 PLC ±0.13		WEIGHT	DRAWING NO		
2 PLC ±0.13		CUSTOMER DRAWING	A100779		
3 PLC ±0.013			C=1445534		
4 PLC ±0.0001			RESTRICTED TO		
ANGLES FINISH			SCALE 5:1		
MATERIAL SEE CALLOUT			SHEET 1 OF 1		
			REV C		