




SEE KEY ORIENTATION


- 5. RECOMMENDED RETAINING BOLT TORQUE: 25-28 IN-LB [2.82-3.16NM]
- 4. THIS CONNECTOR WILL ACCOMMODATE THE FOLLOWING:

CONTACT SIZE	MIN. O.D.	MAX. O.D.	WIRE GAUGE RANGE REF ONLY
20	.040 [1.016]	.095 [2.413]	16 THRU 20 [1.00-.50mm ²]

- 3. PLUG IS SUPPLIED WITH DUST CAP. (NOT SHOWN)
- 2. DIMENSION TOLERANCE: ±.025 [.64]

NOTES: 1. DIMENSIONS ARE IN INCHES [mm].

REV	A	DRC26-50S**	REVISIONS		
SYM	DESCRIPTION		DATE	APPROVED	
NC	NEW RELEASE PER E.O. A14643		12/5/94	RDR	
A	REVISED PER E.O. P16752		7-20-00	RDR	



DRC26-50S01	DRC26-50S02	DRC26-50S03
01	02	03
DRC26-50S04	DRC26-50S05	DRC26-50S06
04	05	06
DRC26-50S07	DRC26-50S08	DRC26-50S09
07	08	09
		DRC26-50S10
		10

- 8. MATERIAL: HOUSING: PLASTIC (BLACK); BOLT: STAINLESS STEEL; CLIP: STEEL.
- 7. THIS PLUG MATES WITH 09D41107L01 THRU 10-**** AND DRC20-50P01 THRU 10 -**** RECEPTACLE. (**** = ALL MODIFICATIONS)
- 6. FOR CONTACT AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS SEE ENVELOPE DRAWING 0425-015-0000.

SIGNATURE & DATE		PLUG 50 CONTACTS, SIZE 20 DRC SERIES	CP EP019		MATL. CODE
DR	V. TOMSA 10/11/94		The Deutsch Company DEUTSCH I.P.D. 3850 INDUSTRIAL AVE. HEMET, CALIF. 92545		DRC26-50S**
CHK	D. Meyer 7/20/00				
PE	D. Meyer 7/20/00				
APPD	R. Reed 7-20-00		B		CODE 11139 SHEET 1 OF 1
SCALE	NONE WT	ENVELOPE			