



DB25 AND XLR FEMALE WIRING CHART

XLR (CHANNEL)	CABLE (COLOR)	PIN 2 (RED)	PIN 3 (BLACK)	PIN 1 (BARE)
1	BROWN	24	12	25
2	RED	10	23	11
3	ORANGE	21	9	22
4	YELLOW	7	20	8
5	GREEN	18	6	19
6	BLUE	4	17	5
7	PURPLE	15	3	16
8	GRAY	1	14	2

PART NO.	CABLE LENGTH "X"
DB25M02XLRF	2.00 FT +/- 1.50 IN
DB25M03XLRF	3.00 FT +/- 1.50 IN
DB25M10XLRF	10.00 FT +/- 1.50 IN

NOTES:

- BREAKOUT CABLE LENGTH: 18.00 +/- 0.75 INCHES. SEE TABLE FOR COLOR.
- THIS PRODUCT COMES COILED AND PACKAGED IN BAG.
- JACKSCREWS ARE SHIPPED UNASSEMBLED. CABLE COMES WITH BOTH #4-40 THREAD (2) AND #M3 THREAD (2) JACKSCREWS.
- MATERIALS:**
 XLR FEMALE CONNECTOR:
 HANDLE - ZINC ALLOY, NICKEL PLATED
 HOUSING AND LATCH - ZINC ALLOY, NICKEL PLATED
 INSULATOR - THERMOPLASTIC, GREEN
 SOCKET CONTACTS - SPECIAL COPPER ALLOY, SILVER PLATED
 H.S. TUBING - THERMOPLASTIC
 DSUB - COPPER ALLOY, NICKEL PLATED WITH GOLD PINS
 JACKSCREWS - STAINLESS STEEL
- THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

					UNLESS OTHERWISE SPECIFIED					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.											
					1. ALL DIMENSIONS IN INCHES					SIZE	WIDTH	MULT	LBS/M	TEMPER							
					- TWO PLACE DECIMALS ±0.02					FINISH		MATERIAL									
					- THREE PLACE DECIMALS ±0.005					SPEC No.		SPEC No.									
										FIRST USED ON		SCALE									
										2:1											
D	26795	7-8-11	TO	TJK						DATE DRAWN	BY	CHKD	APVD								
C	26637	10/11/10	RS	TJK						9/12/06	JGK	RS	TJK								
B	25891	9/9/08	SRC	TJK								11/8/10		11/9/10							
A	25716	10/03/07	JGK	TJK																	
REV	ECO NUMBER	DATE	BY	APVD						NAME		PART No.									
REVISIONS					DO NOT SCALE DRAWING					DB25M TO 8 FEMALE XLR, RoHS		DB25M__XLRF			SHEET 1 OF 1						
															REV D						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Switchcraft:](#)

[DB25M10XLRF](#)