

Heyco® RDD Lockit™ Strain Relief Bushings – Straight-Thru

Snap onto **Round Cables** for Faster Assembly into **Double D Mounting Holes** –
Semi-Automatic Equipment Available
Fit 1/2" Electrical Knock-out Hole




WILL FIT THESE CABLES				PANEL DIMENSIONS				RDD LOCKIT STRAIN RELIEF for Faster Assembly			Corresponding Mounting Hole Plug	
UL Type	AWG/ Conductors	Approximate Size		Mounting Hole Size		Thickness		PART NO. Black	PART NO. White	DESC.	PART NO.	DESC.
See table on page 4-10	various	.290-.385	7,4-9,8	.875 w/.770 flats	22,2 w/19,6 flats	.032 .063 .099 .126 .157	0,8 1,6 2,5 3,2 4,0	1857	1858	RDD 201	2509	DD 875-770
Same as RDD 201 above except →						.078 .140	2,0 3,4	1855	1856	RDD 201-2*	2509	DD 875-770
See table on page 4-10	various	.340-.430	8,6-10,9	.875 w/.770 flats	22,2 w/19,6 flats	.032 .063 .099 .126 .157	0,8 1,6 2,5 3,2 4,0	1861	1862	RDD 301	2509	DD 875-770
Same as RDD 301 above except →						.078 .140	2,0 3,4	1859	1860	RDD 301-2*	2509	DD 875-770
See table on page 4-10	various	.420-.450	10,7-11,4	.875 w/.770 flats	22,2 w/19,6 flats	.032 .063 .099 .126 .157	0,8 1,6 2,5 3,2 4,0	1865	1866	RDD 401	2509	DD 875-770
Same as RDD 401 above except →						.078 .140	2,0 3,4	1882	1883	RDD 401-2*	2509	DD 875-770

Standard color black. Consult Heyco for white and other colors.

*Designed for cast or other mounting holes with rounded edges.

- **Assembly friendly!** Independent of insertion into the panel, RDD Lockit™ Strain Reliefs **self-lock** onto the cable. Preassemble RDD Lockits off line for final assembly at a later time or remote location, for lower installed cost!
- Install easily with fingertip pressure into a standard round or Double D hole. No tools required, even for hand assembly.
- Protect the lifeline of your electric/electronic products by absorbing the forces of push and pull that may be exerted on the flexible power cord. Double D design eliminates the possibility of part rotation under forces of twist.
- Multiple panel locking steps secure Lockit Strain Reliefs into a wide range of panel thicknesses for a **flush, finished fit**.
- Heyco's automated Pre-Assembly Equipment speeds assembly of the RDD onto the cable and thus lowers costs while greatly reducing risk of carpal tunnel syndrome. See pages 4-15 & 4-16.
- Consult Heyco for other wire types and sizes.
- See page 4-38 for corresponding **Mounting Hole Plugs** which can be used to fill blank/unused Mounting Holes and thus allow for a single panel design for multiple applications.
- For Double D Mounting Hole Punches, see page 4-30.



RDD 201, RDD 201-2, RDD 301, RDD 301-2, RDD 401, RDD 401-2

Material	Nylon 6/6
Certifications	Recognized under UL File E15331 Certified by the Canadian Standards Association File 8919
Flammability Rating	94V-2
Temperature Range	-04°F (-18°C) to 221°F (105°C)

*Quick
Specs*