

## nanoLC module - NLC-MOD-USB - 2701195

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Serial connection to PC's USB port for data transfer or software configuration

### Product Description


Slot 1 option module. Connects the Nanoline controller to a Type A USB port. Functions as a serial device and requires special driver included on nanoNavigator CD.

### Your advantages

- ✓ Watchdog timer monitors communication, providing either a warning or fault
- ✓ Password control can limit access: read-only or read/write
- ✓ Serial modules provide a PC connection for configuration purposes and downloading/uploading projects to a basic unit
- ✓ All I/O points, registers, flags, timers, counters, and system flags can be read and written remotely and independently of the program. This enables Nanoline to be used as a simple Modbus I/O block.

RoHS

### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 325400
GTIN	4046356325400

### Technical data

#### Dimensions

Width	24.5 mm
Height	25.5 mm
Depth	49 mm

#### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C

#### Interfaces

## nanoLC module - NLC-MOD-USB - 2701195

### Technical data

#### Interfaces

Interface	USB
Connection method	USB Type B
Transmission length	2 m

#### Supply

Supply voltage	24 V DC (Power available via logic module)
Max. current consumption	18 mA
Typical current consumption	10 mA

#### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

### Approvals

#### Approvals

##### Approvals

##### UL Listed / EAC

##### Ex Approvals

#### Approval details

UL Listed		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 238705
-----------	---	---	---------------

EAC		EAC-Zulassung
-----	---	---------------