



Technical drawing of a 3-hole vertical plate. The drawing shows three circular holes arranged vertically. The top hole is dimensioned with a horizontal distance of .260 [6.6mm] from the left edge. The vertical distance between the center of the top hole and the center of the middle hole is .2405 ± .002 [6.11mm] 2 PLC. The vertical distance between the center of the middle hole and the center of the bottom hole is .3125 ± .004 [7.94mm] 2 PLC. The bottom hole is dimensioned with a horizontal distance of .260 [6.6mm] from the left edge. The drawing includes a dashed centerline and a leader line pointing to the top hole.

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35		
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A		
CENTER CONTACT	BRASS PER ASTM B 16	GOLD PLATE PER MIL-G-45204		
O-RING	FLOUROSILICONE PER MIL-R- 25988, CLASS I, TYPE I.	N/A		
COMPONENT	MATERIAL	FINISH		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ± .005 ± 1°	DRAWN BY MY DATE 5/24/88	 AMP Incorporated. Waltham, MA 02254		
	CHECKED BY KCM 5/26/88 APP'D BY DC 5/26/88			
These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE	TITLE		
	NO. A.P. N/A	OSP 2 HOLE FLANGE MOUNT PLUG RECEPTACLE STRAIGHT TERMINAL		
		SIZE B	CODE IDENT NO. 26805	4551-5022-02
SCALE 4:1		SHEET 1 OF 1		

AMP PART # 1058575-1
SHEET 1 OF 1 REV C