

FO connectors - FOC-V14-C1ZNI-T/SJFP - 1408028

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Push-pull connector (version 14), die-cast zinc, with SC-RJ insert for POF, for cable diameter of 5.5 mm ... 10 mm, cable outlet at the top

Product Features

- ✓ Push-pull ADVANCE connector
- ✓ Locking system to prevent inadvertent removal
- ✓ Highest ESD and EMC resistance for reliable transmission
- ✓



Ethernet



Key commercial data

Packing unit	1 pc
Custom tariff number	85367000
Country of origin	Germany

Technical data

Mechanical characteristics

Standards/specifications	IEC PAS 61076-3-117
Insertion/withdrawal cycles	≥ 50
External cable diameter	5.5 mm ... 10 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (assembly)	-10 °C ... 40 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Degree of protection	IP65/IP67

Material data

Housing material	Zinc die-cast
------------------	---------------

FO connectors - FOC-V14-C1ZNI-T/SJFP - 1408028

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27061803
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	19170122

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002641
ETIM 5.0	EC001122

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501