

12 Mini Stripping Tool



12 80 100 SB

- ▶ for stripping thin copper conductors of 0.25 – 0.8 mm dia.
- ▶ precise stripping because of the tool's stepwise adjustment to the conductor's diameter
- ▶ with wire cutter
- ▶ adjustable length stop from 4.0 – 15.0 mm
- ▶ with locking device
- ▶ shock-resistant plastic body


Article-No.	EAN-	Stripping capacities	g
Length	Code		
mm		Ø mm	g
12 80 100 SB	043119	0.25 – 0.8 30 – 20	50

12 Wire Stripper for Fibre Optics



12 82 130 SB

- ▶ to remove primary and secondary coating of fibre optics
- ▶ burnished head, handles coated with soft plastic



Article-No.	EAN-	Stripping capacities	g
Length	Code		
mm		Ø mm	g
12 82 130 SB	050094	primary coating 0.125, secondary coating 0.25	55

KEVLAR® is a registered Trademark of E. I. du Pont de Nemours and Company

12 Stripping Tool for Fibre Optics



12 85 100 SB

- ▶ to remove primary coating of fibre optics 0.125 mm dia.
- ▶ blade dia. 0.18 mm, hole for cable feeding 0.30 mm dia.
- ▶ adjustable length stop
- ▶ shock-resistant plastic body



Article-No.	EAN-	Stripping capacities	g
Length	Code		
mm		Ø mm	g
12 85 100 SB	043126	to remove primary coating of fibre optics 0.125 mm dia.	40

Removes precisely the primary coating from fibre optics