



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

RPC-2.92 mechanically compatible with  
RPC-SL

RPC-3.50 and SMA  
Interchangeable port connector system

**Documents**

N/A

**Material and plating**

**Connector parts**

- Center contact
- Outer contact RPC-2.92
- Outer contact RPC-SL
- Coupling nut RPC-SL
- Dielectric

**Material**

- Beryllium copper
- Stainless steel
- Stainless steel
- Stainless steel
- PEEK

**Plating**

- Gold, min. 1.27  $\mu$ m, over chemical nickel
- Passivated
- Gold, 0.1  $\mu$ m min.
- Passivated

**ADAPTOR  
RPC-2.92 JACK – RPC-SL PLUG**

**02K1P4-S00S3**

**Electrical data**

Impedance	50 Ω
Frequency	DC to 40 GHz
Return loss	≥ 21 dB, DC to 26.5 GHz ≥ 19 dB, 26.5 GHz to 40 GHz
Insertion loss	≤ 0.05 x √f(GHz) dB
Insulation resistance	≥ 5 GΩ
Center contact resistance	≤ 3.0 mΩ
Outer contact resistance	≤ 2.0 mΩ
Test voltage	750 V rms
Working voltage	250 V rms
RF-leakage	≥ 100 dB up to 1 GHz

**Mechanical data**

Mating cycles RPC-2.92	≥ 500
Mating cycles RPC-SL	≥ 3000
Center contact captivation	≥ 22 N
Coupling test torque RPC-2.92	1.70 Nm
Recommended torque RPC-2.92	0.80 Nm to 1.10 Nm
Recommended torque RPC-SL	2 Nm

**Environmental data**

Temperature range	-40°C to +85°C
Thermal shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition D
Shock	MIL-STD-202, Method 213, Condition I
Moisture resistance	MIL-STD-202, Method 106
2002/95/EC (RoHS)	compliant

**Tooling**

N/A

**Suitable cables**

N/A

**Packing**

Standard	1 pce in box
Weight	27.2 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Herbert Babinger	23.09.04	Krautenbacher J.	19/10/06	c00	06-0478	Wallner Markus	19/10/06
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>		Page 2 / 2