

Technical drawing of the EN60320-3P Inlet connector, showing three views: front, side, and top.

Front View Dimensions:

- Overall height: 52
- Base diameter: 26
- Base thickness: 2.0
- Base width: 30.5
- Base width (inner): 22.5
- Base width (outer): 40

Side View Dimensions:

- Overall height: 67
- Base height: 47.5
- Base thickness: 5.4
- Base width: 3.5
- Base width (inner): 2.0
- Base width (outer): 4.0
- Base width (outer, max): 29

Top View Dimensions:

- Overall width: 6.5
- Overall height: 21

Labels:

- EN60320-3P Inlet
- Soldered terminal
- 2-3.3ø

Packaging Specifications	
Packaging:	Tray, Box
Packaging Quantity:	25
Weight:	55 g

Specifications	
Voltage AC:	250 VAC
Ripple Current:	15 A (AC/DC)
Rated Temperature:	55°C
Temperature Range:	-25/+55°C
Voltage:	250 VDC, 1500 VAC Withstanding Voltage 1 Min. Line to Ground
Leakage Current:	0.5 mA MAX (250 V 60 Hz)
Resistance:	300 MOhms MIN Insulation 500 VDC 1 Min. Line To Ground

Electronic Components
KEMET
CHARGED.®