





LOC		DIST		REVISONS			
GP		P	LTR	DESCRIPTION	DATE	DWN	APVD
		B1		REVISED PER ECO-11-004835	11MAR2011	RK	HMR
		C		REVISED PER ECO-11-020849	17JAN2012	CJV	PAR
		C1		REVISED PER ECO-13-003678	05APR2013	CJV	PAR
		D		REVISED PER ECO-15-017922	04FEB2016	AP	PR

- 1 MATERIALS:
CAGE ASSEMBLY- NICKEL SILVER ALLOY PER ASTM B 122.
EMI SPRING- COPPER ALLOY.
HOUSING- BLACK LCP, UL 94V-0 RATED.
CHICKLET- BLACK LCP, UL 94V-0 RATED.
LIGHT PIPE- POLYCARBONATE, CLEAR.
INSERT - LCP, BLACK, UL 94V-0.
CONTACT- COPPER ALLOY.
- 2 DATUM AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
3. MINIMUM PCB THICKNESS OF 1.5.
- 4 CONTACT FINISH- CONFORMS TO THE REQUIREMENTS OF TE CONNECTIVITY PRODUCT SPECIFICATION 108-2331, BASED ON EIA/ECA-364-1000.01A, (CONTROLLED ENVIRONMENT APPLICATIONS) ON MATING INTERFACE, TIN-LEAD ON NEEDLE EYE.
- 5 CONTACT FINISH- CONFORMS TO THE REQUIREMENTS OF TE CONNECTIVITY PRODUCT SPECIFICATION 108-2331, BASED ON EIA/ECA-364-1000.01A, (CONTROLLED ENVIRONMENT APPLICATIONS) ON MATING INTERFACE, TIN ON NEEDLE EYE.
- 6 FOR HOLE SIZE AND PLATINGS, SEE APPLICATION SPEC 114-13219.
- 7 THE ENTIRE AREA OF THE CONNECTOR FOOTPRINT, INDICATED BY THE DASHED LINE, TO BE CONSIDERED THE KEEPOUT AREA FOR COMPONENTS AND SIGNAL TRACES, TOP SIDE ONLY. TOP SIDE TRACES ALLOWED WITHIN CONNECTOR HOLE PATTERN.
- 8 LIGHT PIPE PAD LAYOUT IS FOR 0805 LOW PROFILE LED PACKAGE WITH A HEIGHT OF 0.8mm.
- 9 EMI SPRING FINISH: 0.8µm MINIMUM MATTE TIN OVER 0.8µm MINIMUM NICKEL, NONPLATED EDGES PERMISSIBLE.
- 10 ADDITIONAL COMPONENT LOCATED WITHIN LATCH PLATE FOR EMI SUPPRESSION.


PRESSION.	YES 		NO LIGHT PIPES	1-2007637-8
			OUTER 2 LIGHT PIPES	1-2007637-7
			INNER 2 LIGHT PIPES	1-2007637-6
			4 LIGHT PIPES	1-2007637-5
	NO		NO LIGHT PIPES	2007637-8
			OUTER 2 LIGHT PIPES	2007637-7
			INNER 2 LIGHT PIPES	2007637-6
			4 LIGHT PIPES	2007637-5
SUPERSEDED	NO		NO LIGHT PIPES	2007637-4
			OUTER 2 LIGHT PIPES	2007637-3
			INNER 2 LIGHT PIPES	2007637-2
			4 LIGHT PIPES	2007637-1
	ENHANCED EMI	FINISH	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009.		DWN M. SHIRK 23JAN2008	TE Connectivity	
DIMENSIONS: mm		CHK D. SZCZESNY 23JAN2008		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. SZCZESNY 23JAN2008	NAME	
0 PLC ±0.10		PRODUCT SPEC	CAGE AND PT CONNECTOR ASSEMBLY, WITH EMI SPRINGS, PRESS FIT, 2X2, STACKED SFP+	
1 PLC ±0.10		108-2331		
2 PLC ±0.10		APPLICATION SPEC	SIZE	
3 PLC ±0.10		114-13219	A100779C=2007637	
4 PLC ±		WEIGHT	RESTRICTED TO	
ANGLES		CUSTOMER DRAWING	SCALE 4:1 SHEET 1 OF 4 REV D	


LOC		DIST		REVISIONS					
GP		00		P	LTR	DESCRIPTION	DATE	DWN	APVD
				-	-	SEE SHEET 1	-	-	-




2007637-5 AND 1-2007637-5
SCALE 3:1



2007637-6 AND 1-2007637-6
SCALE 3:1



2007637-7 AND 1-2007637-7
SCALE 3:1



2007637-8 AND 1-2007637-8
SCALE 3:1

THIS DRAWING IS A CONTROLLED DOCUMENT.
DIMENSIONING AND TOLERANCING
PER ASME Y14.5M-2009

DIMENSIONS:
mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC ±0.10
1 PLC ±0.10
2 PLC ±0.10
3 PLC ±0.10
4 PLC ±
ANGLES ±
FINISH

MATERIAL

DWN
M. SHIRK
23JAN2008

CHK
D. SZCZESNY
23JAN2008

APVD
D. SZCZESNY
23JAN2008

PRODUCT SPEC
108-2331

APPLICATION SPEC
114-13219

WEIGHT
-

CUSTOMER DRAWING

NAME
CAGE AND PT CONNECTOR ASSEMBLY,
WITH EMI SPRINGS,
PRESS FIT, 2X2, STACKED SFP+

SIZE
A1

CAGE CODE
00779

DRAWING NO
C=2007637

RESTRICTED TO
-


SCALE
4:1

SHEET
2


OF
4

REV
D


TE Connectivity




LOC		DIST		REVISIONS				
GP		00		P	LTR	DESCRIPTION		DATE
						SEE SHEET 1		



DETAIL G
CONNECTOR HOUSING
KEEPOUT ZONE
2X INDIVIDUALLY
SCALE 10:1



RECOMMENDED PANEL CUTOUT
AND PC BOARD, PANEL POSITION
SCALE 2:1



SECTION U-U

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009				DWN M. SHIRK 23JAN2008	TE Connectivity			
TOLERANCES UNLESS OTHERWISE SPECIFIED:				CHK D. SZCZESNY 23JAN2008				
DIMENSIONS:				APVD D. SZCZESNY 23JAN2008	NAME CAGE AND PT CONNECTOR ASSEMBLY, WITH EMI SPRINGS, PRESS FIT, 2X2, STACKED SFP+			
mm				PRODUCT SPEC	SIZE			
0 PLC ±0.10				108-2331	CAGE CODE			
1 PLC ±0.10				APPLICATION SPEC	DRAWING NO			
2 PLC ±0.10				114-13219	RESTRICTED TO			
3 PLC ±0.10				WEIGHT	A100779			
4 PLC ±				CUSTOMER DRAWING	SCALE 4:1			
ANGLES FINISH					SHEET 4 OF 4			
MATERIAL					REV D			