


JKL LAMP NUMBER	VOLTS RATED	WATTS	INITIAL MSCP	INITIAL LUMENS	AVERAGE LIFE HRS.	FILAMENT TYPE
6S6-12V	12	6	3.58	45.0	1,500	C-2V
6S6-30V	30	6	3.98	50.0	1,500	C-2V
6S6-120V	120	6	3.18	40.0	1,500	C-7A
6S6-145V	145	6	3.18	40.0	1,500	C-7A
6S6-155V	155	6	3.18	40.0	1,500	C-7A
10S6-230V	230	10	5.97	75.0	1,500	C-1
10S6-250V	250	10	5.97	75.0	1,500	C-1

<b>METRIC</b>		DIMENSIONS ARE IN MILLIMETERS		<b>JKL COMPONENTS CORPORATION</b>					
 THIRD ANGLE PROJECTION		TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0						TITLE <b>S-6 MINIATURE CANDELABRA SCREW BASE LAMP</b>	
DRAWN BY L. WENGSTROM		APPVD BY DATE Q.C. 3/1/01		SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>SCREW BASE CANDELABRA S-6</b>			
RELEASED		3/1/01		SCALE <b>NONE</b>		RELEASED DATE 3/1/01	REVISION DATE	REV. NO.	SHEET 1 OF 1
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED					