

SFSKA6M00CF00-R3










Appearance & Shape







Features

SMD ceramic filter SFSKA_CF is a small and thin SMD filter sealed with a metal cap. Recommended for LCD-TVs, and small and thin tuners.

Features

- 1. High attenuation outside bandwidth.
- 2. Small and thin package.
- 3. Reflow-solderable.



Other Usage

Audio Visual Equipment



Packaging Information

Packaging	Specifications	Minimum Order Quantity
-R0	330mm Embossed Tape	3000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL: http://www.murata.com/



SFSKA6M00CF00-R3




Operating Temperature Range	-20°C to 80°C
Shape	SMD
Elements	1
Center Frequency	6.000MHz
Nominal Center Value	Yes
3dB Bandwidth	fn±60kHzmin.
Stop Bandwidth	600kHz
Spurious Attenuation	25dB[within 0 to fn]
Insertion Loss	6.0dBmax.
Input/Output Impedance	470Ω






SFSKA6M00CF00-R3








Frequency Characteristics

Spurious Response



C2=10pF (Including stray capacitance and Input capacitance of RF Voltmeter) E1: S.S.G. Output voltage

Measurement Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

