




REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
H6		REVISED PER ECO-11-018497	09SEP2011	DLD	DCM
H7		REVISED PER ECO-14-015177	15OCT2014	DLD	DCM

- △ MATERIAL:
- HARNESS - 35% GLASS FILLED PA66, BLACK
ALT MAT'L - 30% GLASS FILLED sPS, BLACK
- SPACER - 40% GLASS FILLED PPS, RED
ALT MAT'L - 30% GLASS FILLED sPS, RED
- COVER - 35% GLASS FILLED PA66, BLACK
ALT MAT'L - 30% GLASS FILLED LCP, BLACK
- CAM LEVER - 35% GLASS FILLED NYLON, GRAY
GROMMET - SILICONE, BROWN
PERIMETER SEAL - SILICONE, GREEN
2. CAM LEVER AND SPACER ARE SHIPPED IN PRE-LATCH POSITION.
- △ 3. SEE PINOUT CHART FOR CLOSED CIRCUIT CONFIGURATIONS.
- △ 4. CAVITIES WITH A NUMERIC SYMBOL INDICATES CLOSED TERMINAL LOCATIONS.
BLANK CAVITIES INDICATE OPEN TERMINAL HOLE LOCATIONS.

CHART FOR CLOSED CIRCUIT CONFIGURATIONS
SHEET 2

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. VESTAL	15OCT2003	TE Connectivity	
		CHK D. STRAUSSER	15OCT2003		
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	
mm		0 PLC ±.3 1 PLC ±0.3 2 PLC ±0.10 3 PLC ±. 4 PLC ±. ANGLES ±1° FINISH		PRODUCT SPEC	
				APPLICATION SPEC	
MATERIAL		WEIGHT		SIZE	
-		-		A100779C=1438083	
		CUSTOMER DRAWING		RESTRICTED TO	
				SCALE 3:1 SHEET 1 OF 2 REV H7	

PIN-OUT CHART KEYING OPTION "B" PIN-OUT CHART KEYING OPTION "A" 4805 (3/13)