



Quality Products. Service Excellence.

20 Amp Horizontal Rackmount Outlet Strip 1589-RF-RR Series

Front or Rear Mounted Receptacles


Features

- Designed for power distribution from front or rear of the unit.
- 1U horizontal 19" rackmount installation.
- Available with on/off switch or red pilot light to indicate power on.
- Available in black powder coat finish.



Specifications

- Heavy duty 12 gauge wire cord - 12/3 SJT type for extreme temperature ranges and integral molded plug.
- Heavy-duty black receptacles rated for 20A, 125VAC service (NEMA 5-20R, Single T-Slot).
- Plug types available are NEMA 5-20P straight blade or NEMA L5-20P locking type.
- Includes 20 Amp, 125 VAC circuit breaker to prevent accidental overload.
- CSA certified, Standards C22.2 (No. 21-95 and No. 42-99)
- UL/cUL recognized Standard UL1363 file No. E166039 & CSA C22.2 No. 308-14



Accessories

- Mounting Hardware
- Rail Depth Adapter Kit



| On/Off Switch Part No. | Illuminated Light Only Part No. | Overall Dimensions | | | Number of Outlets | | NEMA Type | | Plug Blade Type | Cord Length | Rack Units |
|---------------------------|---------------------------------------|--------------------|-------|-------|-------------------|------|-----------|--------|-----------------------|----------------|---------------|
| | | Height | Width | Depth | Front | Rear | Outlet | Plug | | | |
| 1589H6C1BKRF | 1589T6C1BKRF | 1.72 | 19.00 | 2.66 | 6 | 0 | 5-20R | L5-20P | Locking | 6 ft | 1U |
| 1589H6D1BKRF | 1589T6D1BKRF | 1.72 | 19.00 | 2.66 | 6 | 0 | 5-20R | L5-20P | Locking | 15 ft | 1U |
| 1589H6F1BKRF | 1589T6F1BKRF | 1.72 | 19.00 | 2.66 | 6 | 0 | 5-20R | 5-20P | Straight | 6 ft | 1U |
| 1589H6G1BKRF | 1589T6G1BKRF | 1.72 | 19.00 | 2.66 | 6 | 0 | 5-20R | 5-20P | Straight | 15 ft | 1U |
| 1589H8C1BKRF | 1589T8C1BKRF | 1.72 | 19.00 | 2.66 | 8 | 0 | 5-20R | L5-20P | Locking | 6 ft | 1U |
| 1589H8D1BKRF | 1589T8D1BKRF | 1.72 | 19.00 | 2.66 | 8 | 0 | 5-20R | L5-20P | Locking | 15 ft | 1U |
| 1589H8F1BKRF | 1589T8F1BKRF | 1.72 | 19.00 | 2.66 | 8 | 0 | 5-20R | 5-20P | Straight | 6 ft | 1U |

| On/Off Switch Part No. | Illuminated Light Only Part No. | Overall Dimensions | | | Number of Outlets | | NEMA Type | | Plug Blade Type | Cord Length | Rack Units |
|---------------------------|---------------------------------------|--------------------|-------|-------|-------------------|------|-----------|--------|-----------------------|----------------|---------------|
| | | Height | Width | Depth | Front | Rear | Outlet | Plug | | | |
| 1589H8G1BKRF | 1589T8G1BKRF | 1.72 | 19.00 | 2.66 | 8 | 0 | 5-20R | 5-20P | Straight | 15 ft | 1U |
| 1589H6C1BKRR | 1589T6C1BKRR | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-20R | L5-20P | Locking | 6 ft | 1U |
| 1589H6D1BKRR | 1589T6D1BKRR | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-20R | L5-20P | Locking | 15 ft | 1U |
| 1589H6F1BKRR | 1589T6F1BKRR | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-20R | 5-20P | Straight | 6 ft | 1U |
| 1589H6G1BKRR | 1589T6G1BKRR | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-20R | 5-20P | Straight | 15 ft | 1U |
| 1589H8C1BKRR | 1589T8C1BKRR | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-20R | L5-20P | Locking | 6 ft | 1U |
| 1589H8D1BKRR | 1589T8D1BKRR | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-20R | L5-20P | Locking | 15 ft | 1U |
| 1589H8F1BKRR | 1589T8F1BKRR | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-20R | 5-20P | Straight | 6 ft | 1U |
| 1589H8G1BKRR | 1589T8G1BKRR | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-20R | 5-20P | Straight | 15 ft | 1U |

Data subject to change without notice

© 2020. Hammond Manufacturing Ltd. All rights reserved.