

# Fluke 59 MAX/59 MAX+ Infrared Thermometer

Fits your budget. Fits your job.

With 65 years of expertise as the leader in the test tools industry, Fluke has built the 59 MAX and 59 MAX+ IR thermometers with the precision you need to do your job accurately and within your budget. Designed to withstand a 1 meter drop, you can count on these lightweight, compact IR thermometers to work when you need them.



## Technical Data

### Product highlights

- Precise laser technology for more accurate and repeatable measurements
- Large, easy-to-read backlit LCD display for easy viewing
- Small and lightweight design fits easily into your tool box
- IP40 rated for extra protection
- 10:1 Distance to Spot ratio, 59 MAX+ (8:1 Distance to Spot ratio, 59 MAX)
- Displays the minimum, maximum or average temperature, or the difference between two measurements
- Hi and Lo alarms for rapid display of measurements outside the limits
- Powered by one (1) AA battery
- One year warranty

## Specifications

	<b>59 MAX</b>	<b>59 MAX+</b>
<b>Temperature range</b>	-30 °C to 350 °C (-22 °F to 662 °F)	-30 °C to 500 °C (-22 °F to 932 °F)
<b>Accuracy (Calibration geometry with ambient temperature 23 °C ±2 °C)</b>	≥ 0 °C: ± 2.0 °C or ± 2.0 % of reading, whichever is greater	≥ 0 °C: ± 1.5 °C or ± 1.5 % of reading, whichever is greater
	≥ -10 °C to <0 °C: ± 2.0 °C	≥ -10 °C to <0 °C: ± 2.0 °C
	< -10 °C: ± 3.0 °C	< -10 °C: ± 3.0 °C
	≥ 32 °F: ± 4.0 °F or ± 2.0 % of reading, whichever is greater	≥ 32 °F: ± 3.0 °F or ± 1.5 % of reading, whichever is greater
	≥ 14 °F to <32 °F: ± 4.0 °F	≥ 14 °F to <32 °F: ± 4.0 °F
	< 14 °F: ± 6.0 °F	< 14 °F: ± 6.0 °F
<b>Response time (95 %)</b>	<500 ms (95 % of reading)	< 500 ms (95 % of reading)
<b>Spectral response</b>	8 μm to 14 μm	
<b>Emissivity</b>	0.10 to 1.00	
<b>Distance to spot ratio</b>	8:1 (calculated at 90 % energy)	10:1 (calculated at 90 % energy)
<b>Display resolution</b>	0.1 °C (0.2 °F)	
<b>Repeatability (% of reading)</b>	±1.0 % of reading or ±1.0 °C (±2.0 °F), whichever is greater	±0.8 % of reading or ±1.0 °C (±2.0 °F), whichever is greater
<b>General specifications</b>		
<b>Power</b>	1 AA IEC LR06 Battery	
<b>Batter life</b>	12 hours with laser and backlight on	
<b>Weight</b>	220 g (7.76 oz)	
<b>Size</b>	(156 x 80 x 50) mm (6.14 x 3.15 x 2) inches	
<b>Operating temperature</b>	0 °C to 50 °C (32 °F to 122 °F)	
<b>Storage temperature</b>	-20 °C to +60 °C (-4 °F to 140 °F), (without battery)	
<b>Operating humidity</b>	10 % to 90 % RH non-condensing @ 30 °C (86 °F)	
<b>Operating altitude</b>	2000 meters above mean sea level	
<b>Storage altitude</b>	12,000 meters above mean sea level	
<b>Drop test</b>	1 m	
<b>Safety specifications</b>		
<b>Ingress protection rating</b>	IP40 per IEC 60529	
<b>Vibration and shock</b>	IEC 68-2-6 2.5 g, 10 to 200 Hz, IEC 68-2-27, 50 g, 11 ms	
<b>Compliance</b>	EN/IEC 61010-1	
<b>Laser safety</b>	FDA and EN 60825-1 Class II	
<b>Electromagnetic compatibility</b>	61326-1 EN 61326-2	



**Ordering information**

Fluke 59 MAX Infrared Thermometer  
 Fluke 59 MAX+ Infrared Thermometer

**Included:**

Thermometer, One (1) AA battery,  
 registration card and user instructions.

**Fluke.** *The Most Trusted Tools  
 in the World.*

**Fluke Corporation**

PO Box 9090, Everett, WA 98206 U.S.A.

**Fluke Europe B.V.**

PO Box 1186, 5602 BD  
 Eindhoven, The Netherlands

**For more information call:**

In the U.S.A. (800) 443-5853 or

Fax (425) 446-5116

In Europe/M-East/Africa +31 (0) 40 2675 200 or

Fax +31 (0) 40 2675 222

In Canada (800)-36-FLUKE or

Fax (905) 890-6866

From other countries +1 (425) 446-5500 or

Fax +1 (425) 446-5116

Web access: <http://www.fluke.com>

©2013 Fluke Corporation.

Specifications subject to change without notice.

Printed in U.S.A. 6/2013 6000025A\_EN

**Modification of this document is not permitted  
 without written permission from Fluke Corporation.**