

PAGE **1/2**

ISSUE **24-11-16**

SERIE : **SPnT**

PART NUMBER : **R574813645**

RF CHARACTERISTICS

Number of ways : **6**
Frequency range : **0 - 40 GHz**
Impedance : **50 Ohms**

Frequency (GHz)	DC - 6	6 - 12.4	12.4 - 18	18 - 26.5	26.5 - 40
VSWR max	1.30	1.40	1.50	1.70	2.20
Insertion loss max	0.20 dB	0.40 dB	0.50 dB	0.70 dB	1.10 dB
Isolation min	70 dB	60 dB	60 dB	55 dB	50 dB
Average power (*)	40 W	30 W	25 W	15 W	5 W

TERMINATION IMPEDANCE : **50 Ohms**
TERM. AVG. POWER AT 25° C : **1 W per termination / 3 W total power**

ELECTRICAL CHARACTERISTICS

Actuator : **NORMALLY OPEN**
Nominal current ** : **102 mA**
Actuator voltage (Vcc) : **28V (24 to 30V) / POSITIVE COMMON**
Terminals : **25 pins D-SUB male connector**
Indicator rating : **1 W / 30 V / 100 mA**

MECHANICAL CHARACTERISTICS

Connectors : **SMA 2.9 female per MIL-C 39012**
Life : **2.000.000 cycles per position**
Switching Time*** : **< 15 ms**
Construction : **Splashproof**
Weight : **< 250 g**

ENVIRONMENTAL CHARACTERISTICS

Operating temperature range : **-40°C to +85°C**
Storage temperature range : **-55°C to +85°C**

(*) Average power at 25°C per RF Path)
(**) At 25° C ±10%)
(***) Nominal voltage ; 25° C)




PAGE 2/2

ISSUE 24-11-16

SERIE : SPnT


PART NUMBER : **R574813645**

DRAWING



Voltage	RF Continuity	Ind.
+C -1	IN $\leftrightarrow$ 1	D.G
+C -2	IN $\leftrightarrow$ 2	D.H
+C -3	IN $\leftrightarrow$ 3	D.I
+C -4	IN $\leftrightarrow$ 4	D.J
+C -5	IN $\leftrightarrow$ 5	D.E
+C -6	IN $\leftrightarrow$ 6	D.F

LABEL



General tolerances : ± 0.5 mm

SCHEMATIC DIAGRAM

