RAFI

RAFIX 22 FSR - Keylock switch, latching, 1 x 90°, V shape

1.30.285.321/0100

General information	
Color of front ring	black
Form of collar	round

Dimensions	
Dimensions of collar	ø 31.3 mm
Overall height	45.1 mm
Mounting hole	22.3 mm
Key grid	35 x 35 mm

Mechanical design	
Mounting	ring nut
Contact function	latching
Illuminability	no
Wafers	5
Number of locking types	18
Lock type	001
Main key	on request
Rotating angle	1 x 90°, V shape
Key removal position	0+1
Torque for nut ring	1.2 Nm

Mechanical characteristics	
Torque max.	1.3 Nm

Other specifications	
Degree of protection from front side	IP65 (DIN EN 60529)
Ambient temp. operating min.	-40 °C
Ambient temp. operating max.	+85 °C
Storage temperature min.	-40 °C
Storage temperature max.	+85 °C
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Salt spray	IEC 600 68-2-11
ROHS compliant	yes
REACH compliant	yes

RAFI

Panel cut-out to IEC 60947-5-1

$3.20_0^{+0.20}$

$\varnothing\ 22.30_0^{+0.40}$

$24.10_0^{+0.40}$

Schutzkappe/
protective cap

45.1

21.5

1.0-3.0

M 22.0x1.0

$\varnothing\ 31.3$

0   1