

OR USED AS A BASIS FOR  
WITHOUT PRIOR WRITTEN  
FROM KEYSTONE ELECTRONICS

REEL DIA. REF.

FEED DIRECTION

.500 [12.7] MIN.  
DIA. HOLE THRU

$\pm .005$  [ $\pm 0.13$ ]  
PITCH

$\pm .005$  [ $\pm 0.13$ ]  
.157 [4.0]

$\pm .005$  [ $\pm 0.13$ ]  
.059 [1.5] DIA.  
HOLE (TYP.)

.079 [2.0]

.236 [6.0]  
REF.

WIDTH  
 $\pm .005$  [ $\pm 0.13$ ]

FEED DIRECTION

.016 [0.4]  
REF.

<h1>KEYSTONE ELECTRONICS CORP.</h1> <p>www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900</p>			
PART NAME <h2>1632 SMT HOLDER ON TAPE AND REEL</h2>			
MATERIAL <h2>AS NOTED</h2>			
FINISH <h2>AS NOTED</h2>		DRN BY <h2>NT</h2>	DATE <h2>1.05.11</h2>
		APP'D <h2>LN</h2>	SCALE <h2>X</h2>
TOLERANCES INCH [MM] DECIMAL $\pm .015$ [ $\pm 0.38$ ] ANGULAR $\pm 1^\circ$ UNLESS OTHERWISE SPECIFIED	CODE <h2>C</h2>	DWG NO. <h2>504TR</h2>	