



**Quick Reference**

Search by part #

Check distributor part inventory

**Products**

Browse Products

-By Device -

-By Product Line-

-Attachment Methods

-Interface Materials -

-Accessories -

**Useful Links**

[MSDS Safety Sheets](#)

[How to Order?](#)

[Find Sales Rep](#)

[Find Distributor](#)

[Sample Request](#)

[Quote Request](#)

[Catalog Request](#)

[Building a Part #](#)

[Part # Cross Ref](#)

Accessories  
Standard Mounting Pads

The following Mounting Pads are for use with T08

|   |  |
|---|--|
| <p><b>7717-157TG</b></p> <p>(Teflon)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 6.35 (0.250)</p> <p>Thickness: 0.25 (0.010)</p> <p>RoHS Compliant</p>                             |  |
| <p><b>7717-153DAPG</b></p> <p>(DAP)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 6.35 (0.250)</p> <p>Thickness: 0.97 (0.038)</p> <p>RoHS Compliant</p>                              |  |
| <p><b>7717-153NG</b></p> <p>(nylon)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 6.35 (0.250)</p> <p>Thickness: 0.97 (0.038)</p> <p>RoHS Compliant</p>                              |  |
| <p><b>7717-152DAPG</b></p> <p>(DAP)</p> <p>Leads: 4-Mar</p> <p>Outside Diameter mm (in): 5.08 (0.200)</p> <p>Thickness: 1.14 (0.045)</p> <p>RoHS Compliant</p>                          |  |
| <p><b>7717-152NG</b></p> <p>(nylon)</p> <p>Leads: 4-Mar</p> <p>Outside Diameter mm (in): 5.08 (0.200)</p> <p>Thickness: 1.14 (0.045)</p> <p>RoHS Compliant</p>                          |  |
| <p><b>7717-124NG</b></p> <p>(nylon)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 5.72 (0.225)</p> <p>Thickness: 0.51 (0.020)</p> <p>RoHS Compliant</p>                              |  |
| <p><b>7717-7DAPG</b></p> <p>(DAP)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 6.35 (0.250)</p> <p>Thickness: 3.18 (0.125)</p> <p>RoHS Compliant</p> <p>Product Change Notice</p>   |  |
| <p><b>7717-7NG</b></p> <p>(nylon)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 6.35 (0.250)</p> <p>Thickness: 3.18 (0.125)</p> <p>RoHS Compliant</p> <p>Product Change Notice</p>   |  |
| <p><b>7717-89DAPG</b></p> <p>(DAP)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 6.35 (0.250)</p> <p>Thickness: 2.03 (0.080)</p> <p>RoHS Compliant</p> <p>Product Change Notice</p>  |  |
| <p><b>7717-89NG</b></p> <p>(nylon)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 6.35 (0.250)</p> <p>Thickness: 2.03 (0.080)</p> <p>RoHS Compliant</p> <p>Product Change Notice</p>  |  |
| <p><b>7717-108DAPG</b></p> <p>(DAP)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 5.26 (0.203)</p> <p>Thickness: 1.78 (0.070)</p> <p>RoHS Compliant</p> <p>Product Change Notice</p> |  |
| <p><b>7717-108NG</b></p> <p>(nylon)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 5.26 (0.203)</p> <p>Thickness: 1.78 (0.070)</p> <p>RoHS Compliant</p> <p>Product Change Notice</p> |  |
| <p><b>7717-18DAPG</b></p> <p>(DAP)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 5.08 (0.200)</p> <p>Thickness: 2.54 (0.100)</p> <p>RoHS Compliant</p> <p>Product Change Notice</p>  |  |
| <p><b>7717-18NG</b></p> <p>(nylon)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 5.08 (0.200)</p> <p>Thickness: 2.54 (0.100)</p> <p>RoHS Compliant</p> <p>Product Change Notice</p>  |  |
| <p><b>7717-16NG</b></p> <p>(nylon)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 5.08 (0.200)</p> <p>Thickness: 0.51 (0.020)</p> <p>RoHS Compliant</p> <p>Product Change Notice</p>  |  |
| <p><b>7717-16DAPG</b></p> <p>(DAP)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 5.08 (0.200)</p> <p>Thickness: 0.51 (0.020)</p> <p>RoHS Compliant</p> <p>Product Change Notice</p>  |  |
| <p><b>7717-112DAPG</b></p> <p>(DAP)</p> <p>Leads: 4-Mar</p> <p>Outside Diameter mm (in): 5.08 (0.200)</p> <p>Thickness: 0.64 (0.025)</p> <p>RoHS Compliant</p>                          |  |
| <p><b>7717-220NG</b></p> <p>(nylon)</p> <p>Leads: 4-Mar</p> <p>Outside Diameter mm (in): 5.84 (0.230)</p> <p>Thickness: 2.03 (0.080)</p> <p>RoHS Compliant</p>                          |  |
| <p><b>7717-239NG</b></p> <p>(nylon)</p> <p>Leads: 4-Mar</p> <p>Outside Diameter mm (in): 6.10 (0.240)</p> <p>Thickness: 457 (0.180)</p> <p>RoHS Compliant</p>                           |  |
| <p><b>7717-46NG</b></p> <p>(nylon)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 5.08 (0.200)</p> <p>Thickness: 1.52 (0.060)</p> <p>RoHS Compliant</p>                               |  |
| <p><b>7717-46DAPG</b></p> <p>(DAP)</p> <p>Leads: 4</p> <p>Outside Diameter mm (in): 5.08 (0.200)</p> <p>Thickness: 1.52 (0.060)</p> <p>RoHS Compliant</p>                               |  |